



AS-i compact module K60 digital A/B slave, 4 DI, IP67 4 x input, maximum 200 mA
4 x M12 socket Y-II assignment Mounting plate 3RK1901-0CA00 must be ordered separately

General technical data	
design of the product	digital I/O modules for operation in the field, IP67 - K60
Type	4 inputs
design of the slave type	A/B slave
I/O configuration	0
ID/ID2 code	A/E
Number I/O sockets	4
type of electrical connection of the inputs and outputs	M12 screw-type terminals
AS interface total current input max	270 mA
operating voltage according to AS-Interface specification	18 ... 31.6 V
Ground terminal	PIN5 of each M12 socket is connected to the grounding wrist strap in the mounting plate using a pin
Addressing	front addressing socket
Delivery note	the modules are delivered without mounting plate
Sensor supply	
type of voltage supply for power supply	using AS-Interface
input voltage	16.5 ... 30 V
property of the sensor supply short-circuit and overload resistant	Yes
ampacity of the sensor supply for all inputs	200 mA
• at ambient temperature 40 °C	
Inputs	
number of digital inputs	4
type of connection technology	2- and 3-wire technology
Input circuit	PNP transistor
type of voltage of the input voltages	DC
Inputs switching level High min	10 V
input current at digital input	6 mA
• for signal <1> minimum	
• with signal <0> maximum	1.5 mA
Inputs	short-circuit and overload resistant
• sensor supply using AS-Interface	
• socket assignment	
— PIN 1	
— PIN 2	
— PIN 3	
— PIN 4	
— PIN 5	
design of the pin assignment of the inputs	Y-II assignment
Outputs	
number of digital outputs	0

Outputs external power supply 24 V DC	not required
Outputs	
• watchdog	not required
Assignment of the data bits	
Assignment of data bits	
• socket	PIN 4 = IN1 (D0), PIN 2 = IN2 (D1)
• socket 2	PIN 4 = IN2 (D1)
• socket 3	PIN 4 = IN3 (D2) , PIN 2 = IN4 (D3)
• socket 4	PIN 4 = IN4 (D3)
• socket 5	not assigned (closed)
• socket 6	not assigned (closed)
• socket 7	not assigned (closed)
• socket 8	not assigned (closed)
Ambient conditions	
ambient temperature	
• during operation	-25 ... +85 °C
• during storage	-40 ... +85 °C
protection class IP	IP67
Display	
Status display	
• display of I/Os	yellow LED
• display of Uaux	not required
• display of AS-Interface/diagnostics	green/red LED
Mechanical data	
width	60 mm
height	152 mm
depth	29 mm
fastening method	standard rail mounting/wall mounting using mounting plate for K60 compact module
shock resistance	15g / 11 ms
Certificates/ approvals	
General Product Approval	EMV



[Confirmation](#)



Marine / Shipping	other	Environment
		



[Confirmation](#)


[Miscellaneous](#)

[Environmental Confirmations](#)

Industrial Communication


Further information
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,...) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK2200-0CQ00-0AA3 Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK2200-0CQ00-0AA3 Service&Support (Manuals, Certificates, Characteristics, FAQs,...)





last modified:

3/11/2024