



AS-I COMPACT MODULE K20, IP67,
A/B-SLAVE, DIGITAL, 2DI/2DO,
2 X INPUT FOR SENSOR(MECHAN./2- OR 3-WIRE) PNP,
SENSOR SUPPLY FROM U_ASI "TOTAL MAX.150MA," 2 X
OUTPUT MAX. 1A OUTPUT SUPPLY FROM DC 24V MAX.
1A FOR ALL OUTPUTS 2XM12-SOCKET

General technical data:

Design of the product		digital I/O modules for operation in the field, IP67 - K20
Type		2 outputs / 2 inputs
Design of the slave type		A/B slave
I/O configuration		B
ID/ID2 code		A/2
Number / I/O sockets		2
Design of the electrical connection / of the inputs and outputs		M12 screw-type terminals
AS interface / total current input / max	mA	270
operating voltage		
• according to AS-Interface specification	V	26.5 ... 31.6
Ground terminal		not available
Addressing		using M12 female connector
AS interface / Connection / Polarity reversal protection		built-in
Note 1		An external additional supply (AUX POWER) of 20 to 30 V DC is required for the supply of the output circuits. The additional supply must comply with VDE 0106 (PELV), protection class III.

Sensor supply:

Type of voltage supply / for the sensor supply		using AS-Interface
--	--	--------------------

Input voltage	V	16.5 ... 30
Characteristic feature of the sensor supply / short-circuit and overload resistant		Yes
Current carrying capacity / of the sensor supply / for all inputs		
• at ambient temperature 40 °C	mA	150
• at ambient temperature 55 °C	mA	70

Inputs:		
Number of digital inputs		2
Type of connection		2- and 3-wire technology
Input circuit		PNP transistor
Type of / input voltages		DC
Inputs / switching level High / min	V	10
Input current / at the digital input		
• for signal <1> / minimum	mA	6
• at signal <0> / maximum	mA	1.5
Inputs		
• sensor supply using AS-Interface		short-circuit and overload resistant
Inputs / socket assignment		
• PIN 1		sensor supply L+
• PIN 2		data input 2
• PIN 3		sensor supply L-
• PIN 4		data input 1
Design of the pin assignment / of the inputs		Y assignement

Outputs:		
Number of digital outputs		2
Voltage type / of output voltages		DC
Outputs / external power supply 24 V DC		shared round cable connection with AS-Interface connection through M12 female connector
Output current / at the digital output / for signal <1> / nominal value	A	1
Outputs / aggregate current		
• max	A	1
Design of the switching output		PNP transistor
Design of the pin assignment / of the outputs		Y assignement
Outputs / socket assignment		2 = output 2, 3 = "-", 4 = output 1
Characteristic feature of the output / short-circuit protected		Yes
Outputs		
• short-circuit protection		built-in
• induction protection		built-in

- watchdog

built-in

Status display

- display of I/Os
- display of Uaux
- display of AS-Interface/diagnostics

yellow LED
green LED
green/red dual LED

Assignment of data bits

- socket
- socket 2
- socket 3
- socket 4

PIN 4 = IN3 (D2), PIN 2 = IN4 (D3)
PIN 4 = OUT1 (D0), PIN 2 = OUT2 (D1)
not available
not available

Ambient conditions:

Ambient temperature

- during operating
- during storage

°C -25 ... +70
°C -40 ... +85

Protection class IP

IP67

Mechanical design:

Width

mm 20

Height

mm 108

Depth

mm 45

Mounting type

no mounting plate required

Certificates/approvals:

AS-Interface certificate

yes

Approvals

UL and CSA requested

General Product Approval

Test Certificates



[Special Test Certificate](#)

Shipping Approval



other



[Confirmation](#)

[Declaration of Conformity](#)

[other](#)

[Environmental Confirmations](#)

Further information:



last change:

Jun 16, 2014