

THERMISTOR MOTOR PROTECTION STANDARD
EVALUATION UNIT AUTO,
1NO+1NC,
UC 24...240V SPRING-LOADED TERMINAL

General technical details:

type of voltage		AC/DC
Supply voltage frequency		
1 / for auxiliary and control current circuit - rated value	Hz	50
2 / for auxiliary and control current circuit - rated value	Hz	60
Control supply voltage		
1 - at 50 Hz / for AC - initial rated value - final rated value - at 60 Hz / for AC - initial rated value - final rated value - for DC - initial rated value - final rated value	V V V V V V	24 240 24 240 24 240
Number of measuring circuits		1
Number of NC contacts / for auxiliary contacts		1
Number of NO contacts / for auxiliary contacts		1
Number of change-over switches / for auxiliary contacts		0
Measurable temperature		
- initial value - final value	°C °C	60 180
Product function		
- reclosing interlock - self-reset - defect storage - reset external		No Yes No No
Item designation / according to DIN EN 61346-2		K

Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		K
Ambient temperature / during operating	°C	-25 ... +60

Mechanical design:

Design of the electrical connection / for auxiliary and control current circuit		spring-loaded terminals
Design of the electrical connection / jumper socket		No
Type of display / LED		Yes
Protection class IP		IP20
Width	mm	22.5
Height	mm	94
Depth	mm	91

Certificates/approvals:

General Product Approval			EMC	For use in hazardous locations	
					
CCC	CSA	GOST	UL	C-TICK	ATEX
Test Certificates		Shipping Approval			
Special Test Certificate					
	DNV	GL	LRS	PRS	RMRS
other					
Declaration of Conformity	other	Environmental Confirmations			

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator



<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RN1010-2CW00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RN1010-2CW00



last change:

Jan 21, 2013