

CONTACTOR,AC-3, 5.5KW/400V,1NO 24V DC, 3-POLE, SIZE S00,  
CAGE CLAMP TERMINAL MULTI-UNIT PACK, 1 PACK = 20 UNITS



Figure similar

|                                                                                     |                 |
|-------------------------------------------------------------------------------------|-----------------|
| product brand name                                                                  | SIRIUS          |
| Product designation                                                                 | power contactor |
| General technical data                                                              |                 |
| Size of contactor                                                                   | S00             |
| Degree of pollution                                                                 | 3               |
| Protection class IP                                                                 |                 |
| • on the front                                                                      | IP20            |
| • of the terminal                                                                   | IP20            |
| Mechanical service life (switching cycles)                                          |                 |
| • of contactor typical                                                              | 30 000 000      |
| • of the contactor with added electronics-compatible auxiliary switch block typical | 5 000 000       |
| • of the contactor with added auxiliary switch block typical                        | 10 000 000      |
| Ambient conditions                                                                  |                 |
| Installation altitude at height above sea level maximum                             | 2 000 m         |

|                                                        |                |
|--------------------------------------------------------|----------------|
| <b>Ambient temperature</b>                             |                |
| • during operation                                     | -25 ... +60 °C |
| <b>Main circuit</b>                                    |                |
| <b>Number of poles for main current circuit</b>        | 3              |
| <b>Number of NO contacts for main contacts</b>         | 3              |
| <b>Number of NC contacts for main contacts</b>         | 0              |
| <b>Operating current</b>                               |                |
| • at AC-1 at 400 V                                     |                |
| — at ambient temperature 40 °C rated value             | 22 A           |
| • at AC-1                                              |                |
| — up to 690 V at ambient temperature 40 °C rated value | 22 A           |
| — up to 690 V at ambient temperature 60 °C rated value | 20 A           |
| • at AC-3                                              |                |
| — at 400 V rated value                                 | 12 A           |
| <b>Operating current</b>                               |                |
| • at 1 current path at DC-1                            |                |
| — at 24 V rated value                                  | 20 A           |
| — at 110 V rated value                                 | 2.1 A          |
| • with 2 current paths in series at DC-1               |                |
| — at 24 V rated value                                  | 20 A           |
| — at 110 V rated value                                 | 12 A           |
| • with 3 current paths in series at DC-1               |                |
| — at 24 V rated value                                  | 20 A           |
| — at 110 V rated value                                 | 20 A           |
| <b>Operating current</b>                               |                |
| • at 1 current path at DC-3 at DC-5                    |                |
| — at 24 V rated value                                  | 20 A           |
| — at 110 V rated value                                 | 0.15 A         |
| • with 2 current paths in series at DC-3 at DC-5       |                |
| — at 110 V rated value                                 | 0.35 A         |
| — at 24 V rated value                                  | 20 A           |
| • with 3 current paths in series at DC-3 at DC-5       |                |
| — at 110 V rated value                                 | 20 A           |
| — at 24 V rated value                                  | 20 A           |
| <b>Operating power</b>                                 |                |
| • at AC-1                                              |                |
| — at 400 V rated value                                 | 13 kW          |
| • at AC-2 at 400 V rated value                         | 5.5 kW         |
| • at AC-3                                              |                |

|                                                                                               |        |
|-----------------------------------------------------------------------------------------------|--------|
| — at 400 V rated value                                                                        | 5.5 kW |
| — at 500 V rated value                                                                        | 5.5 kW |
| — at 690 V rated value                                                                        | 5.5 kW |
| <b>Power loss [W] at AC-3 at 400 V for rated value of the operating current per conductor</b> | 1.24 W |

| Control circuit/ Control                                                              |              |
|---------------------------------------------------------------------------------------|--------------|
| <b>Type of voltage of the control supply voltage</b>                                  | DC           |
| <b>Control supply voltage at DC</b>                                                   |              |
| • rated value                                                                         | 24 V         |
| <b>Operating range factor control supply voltage rated value of magnet coil at DC</b> | 0.85 ... 1.1 |
| <b>Closing power of magnet coil at DC</b>                                             | 3.3 W        |
| <b>Holding power of magnet coil at DC</b>                                             | 3.3 W        |

| Auxiliary circuit                                |                                                 |
|--------------------------------------------------|-------------------------------------------------|
| <b>Number of NC contacts</b>                     |                                                 |
| • for auxiliary contacts                         |                                                 |
| — instantaneous contact                          | 0                                               |
| <b>Number of NO contacts</b>                     |                                                 |
| • for auxiliary contacts                         |                                                 |
| — instantaneous contact                          | 1                                               |
| <b>Operating current at AC-12 maximum</b>        | 10 A                                            |
| <b>Operating current at AC-15</b>                |                                                 |
| • at 230 V rated value                           | 6 A                                             |
| • at 400 V rated value                           | 3 A                                             |
| <b>Operating current at DC-12</b>                |                                                 |
| • at 60 V rated value                            | 6 A                                             |
| • at 110 V rated value                           | 3 A                                             |
| • at 220 V rated value                           | 1 A                                             |
| <b>Operating current at DC-13</b>                |                                                 |
| • at 24 V rated value                            | 10 A                                            |
| • at 60 V rated value                            | 2 A                                             |
| • at 110 V rated value                           | 1 A                                             |
| • at 220 V rated value                           | 0.3 A                                           |
| <b>Contact reliability of auxiliary contacts</b> | 1 faulty switching per 100 million (17 V, 1 mA) |

| Short-circuit protection                                        |                  |
|-----------------------------------------------------------------|------------------|
| <b>Design of the fuse link</b>                                  |                  |
| • for short-circuit protection of the main circuit              |                  |
| — with type of coordination 1 required                          | fuse gL/gG: 35 A |
| — with type of assignment 2 required                            | fuse gL/gG: 20 A |
| • for short-circuit protection of the auxiliary switch required | fuse gL/gG: 10 A |

## Installation/ mounting/ dimensions

|                                                                                                                                         |                                                                                        |
|-----------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| <b>Mounting type</b>                                                                                                                    | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022 |
| <ul style="list-style-type: none"> <li>• Side-by-side mounting</li> </ul>                                                               | Yes                                                                                    |
| <b>Height</b>                                                                                                                           | 60 mm                                                                                  |
| <b>Width</b>                                                                                                                            | 45 mm                                                                                  |
| <b>Depth</b>                                                                                                                            | 73 mm                                                                                  |
| <b>Required spacing</b>                                                                                                                 |                                                                                        |
| <ul style="list-style-type: none"> <li>• for grounded parts <ul style="list-style-type: none"> <li>— at the side</li> </ul> </li> </ul> | 6 mm                                                                                   |

## Connections/Terminals

|                                                                                                                                                     |                                    |
|-----------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|
| <b>Type of electrical connection</b>                                                                                                                |                                    |
| <ul style="list-style-type: none"> <li>• for main current circuit</li> </ul>                                                                        | spring-loaded terminals            |
| <ul style="list-style-type: none"> <li>• for auxiliary and control current circuit</li> </ul>                                                       | spring-loaded terminals            |
| <b>Type of connectable conductor cross-sections</b>                                                                                                 |                                    |
| <ul style="list-style-type: none"> <li>• for main contacts <ul style="list-style-type: none"> <li>— solid</li> </ul> </li> </ul>                    | 2x (0.25 ... 2.5 mm <sup>2</sup> ) |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— single or multi-stranded</li> </ul> </li> </ul>                    | 2x (0,25 ... 2,5 mm <sup>2</sup> ) |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— finely stranded with core end processing</li> </ul> </li> </ul>    | 2x (0.25 ... 1.5 mm <sup>2</sup> ) |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— finely stranded without core end processing</li> </ul> </li> </ul> | 2x (0.25 ... 2.5 mm <sup>2</sup> ) |
| <ul style="list-style-type: none"> <li>• at AWG conductors for main contacts</li> </ul>                                                             | 2x (24 ... 14)                     |
| <b>Type of connectable conductor cross-sections</b>                                                                                                 |                                    |
| <ul style="list-style-type: none"> <li>• for auxiliary contacts <ul style="list-style-type: none"> <li>— solid</li> </ul> </li> </ul>               | 2x (0.25 ... 2.5 mm <sup>2</sup> ) |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— finely stranded with core end processing</li> </ul> </li> </ul>    | 2x (0.25 ... 1.5 mm <sup>2</sup> ) |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— finely stranded without core end processing</li> </ul> </li> </ul> | 2x (0.25 ... 2.5 mm <sup>2</sup> ) |
| <ul style="list-style-type: none"> <li>• at AWG conductors for auxiliary contacts</li> </ul>                                                        | 2x (24 ... 14)                     |

## Certificates/approvals

| General Product Approval | Functional Safety/Safety of Machinery | Declaration of Conformity |
|--------------------------|---------------------------------------|---------------------------|
|--------------------------|---------------------------------------|---------------------------|



[Baumusterprüfbescheinigung](#)



| Test Certificates | Shipping Approval |
|-------------------|-------------------|
|-------------------|-------------------|

[spezielle Prüfbescheinigungen](#)

[sonstig](#)



| Shipping Approval | other |
|-------------------|-------|
|-------------------|-------|



[Umweltbestätigung](#)

[Bestätigungen](#)

[sonstig](#)

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT1017-2BB41-Z W98>

##### Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT1017-2BB41-Z W98>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT1017-2BB41-Z W98>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT1017-2BB41-Z W98&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT1017-2BB41-Z W98&lang=en)



last modified:

10/17/2016