

CONTACTOR, AC-3, 5.5KW/400V, 110V AC 50/60HZ, 3-POLE,  
SIZE S0, SCREW TERMINAL MULTI-UNIT PACKAGING 1 PACK =  
48 UNITS



|                                                                                     |                 |
|-------------------------------------------------------------------------------------|-----------------|
| product brand name                                                                  | SIRIUS          |
| Product designation                                                                 | power contactor |
| General technical data                                                              |                 |
| Size of contactor                                                                   | S0              |
| Degree of pollution                                                                 | 3               |
| Protection class IP                                                                 |                 |
| • on the front                                                                      | IP20            |
| • of the terminal                                                                   | IP20            |
| Mechanical service life (switching cycles)                                          |                 |
| • of contactor typical                                                              | 10 000 000      |
| • of the contactor with added electronics-compatible auxiliary switch block typical | 5 000 000       |
| • of the contactor with added auxiliary switch block typical                        | 10 000 000      |
| Ambient conditions                                                                  |                 |
| Installation altitude at height above sea level maximum                             | 2 000 m         |
| Ambient temperature                                                                 |                 |
| • during operation                                                                  | -25 ... +60 °C  |

| Main circuit                                                                                                                                                                                                                    |                  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| Number of poles for main current circuit                                                                                                                                                                                        | 3                |
| Number of NO contacts for main contacts                                                                                                                                                                                         | 3                |
| Number of NC contacts for main contacts                                                                                                                                                                                         | 0                |
| Operating current                                                                                                                                                                                                               |                  |
| <ul style="list-style-type: none"> <li>at AC-1 at 400 V <ul style="list-style-type: none"> <li>at ambient temperature 40 °C rated value</li> </ul> </li> </ul>                                                                  | 40 A             |
| <ul style="list-style-type: none"> <li>at AC-1 <ul style="list-style-type: none"> <li>up to 690 V at ambient temperature 40 °C rated value</li> <li>up to 690 V at ambient temperature 60 °C rated value</li> </ul> </li> </ul> | 40 A<br>35 A     |
| <ul style="list-style-type: none"> <li>at AC-3 <ul style="list-style-type: none"> <li>at 400 V rated value</li> </ul> </li> </ul>                                                                                               | 12 A             |
| Operating current                                                                                                                                                                                                               |                  |
| <ul style="list-style-type: none"> <li>at 1 current path at DC-1 <ul style="list-style-type: none"> <li>at 24 V rated value</li> <li>at 110 V rated value</li> </ul> </li> </ul>                                                | 35 A<br>4.5 A    |
| <ul style="list-style-type: none"> <li>with 2 current paths in series at DC-1 <ul style="list-style-type: none"> <li>at 24 V rated value</li> <li>at 110 V rated value</li> </ul> </li> </ul>                                   | 35 A<br>35 A     |
| <ul style="list-style-type: none"> <li>with 3 current paths in series at DC-1 <ul style="list-style-type: none"> <li>at 24 V rated value</li> <li>at 110 V rated value</li> </ul> </li> </ul>                                   | 35 A<br>35 A     |
| Operating current                                                                                                                                                                                                               |                  |
| <ul style="list-style-type: none"> <li>at 1 current path at DC-3 at DC-5 <ul style="list-style-type: none"> <li>at 24 V rated value</li> <li>at 110 V rated value</li> </ul> </li> </ul>                                        | 20 A<br>2.5 A    |
| <ul style="list-style-type: none"> <li>with 2 current paths in series at DC-3 at DC-5 <ul style="list-style-type: none"> <li>at 110 V rated value</li> <li>at 24 V rated value</li> </ul> </li> </ul>                           | 15 A<br>35 A     |
| <ul style="list-style-type: none"> <li>with 3 current paths in series at DC-3 at DC-5 <ul style="list-style-type: none"> <li>at 110 V rated value</li> <li>at 24 V rated value</li> </ul> </li> </ul>                           | 35 A<br>35 A     |
| Operating power                                                                                                                                                                                                                 |                  |
| <ul style="list-style-type: none"> <li>at AC-1 <ul style="list-style-type: none"> <li>at 400 V rated value</li> </ul> </li> </ul>                                                                                               | 23 kW            |
| <ul style="list-style-type: none"> <li>at AC-2 at 400 V rated value</li> </ul>                                                                                                                                                  | 5.5 kW           |
| <ul style="list-style-type: none"> <li>at AC-3 <ul style="list-style-type: none"> <li>at 400 V rated value</li> <li>at 500 V rated value</li> </ul> </li> </ul>                                                                 | 5.5 kW<br>7.5 kW |

|                                                                                               |                                                 |
|-----------------------------------------------------------------------------------------------|-------------------------------------------------|
| — at 690 V rated value                                                                        | 7.5 kW                                          |
| <b>Power loss [W] at AC-3 at 400 V for rated value of the operating current per conductor</b> | 0.5 W                                           |
| <b>Control circuit/ Control</b>                                                               |                                                 |
| <b>Type of voltage of the control supply voltage</b>                                          | AC                                              |
| <b>Control supply voltage at AC</b>                                                           |                                                 |
| • at 50 Hz rated value                                                                        | 110 V                                           |
| • at 60 Hz rated value                                                                        | 110 V                                           |
| <b>Control supply voltage frequency 1 rated value</b>                                         | 50 Hz                                           |
| <b>Control supply voltage frequency 2 rated value</b>                                         | 60 Hz                                           |
| <b>Operating range factor control supply voltage rated value of magnet coil at AC</b>         |                                                 |
| • at 50 Hz                                                                                    | 0.8 ... 1.1                                     |
| • at 60 Hz                                                                                    | 0.85 ... 1.1                                    |
| <b>Apparent pick-up power of magnet coil at AC</b>                                            | 64 V·A                                          |
| <b>Inductive power factor with closing power of the coil</b>                                  | 0.72                                            |
| <b>Apparent holding power of magnet coil at AC</b>                                            | 8.4 V·A                                         |
| <b>Inductive power factor with the holding power of the coil</b>                              | 0.24                                            |
| <b>Auxiliary circuit</b>                                                                      |                                                 |
| <b>Number of NC contacts</b>                                                                  |                                                 |
| • for auxiliary contacts                                                                      |                                                 |
| — instantaneous contact                                                                       | 0                                               |
| <b>Number of NO contacts</b>                                                                  |                                                 |
| • for auxiliary contacts                                                                      |                                                 |
| — instantaneous contact                                                                       | 0                                               |
| <b>Operating current at AC-12 maximum</b>                                                     | 10 A                                            |
| <b>Operating current at AC-15</b>                                                             |                                                 |
| • at 230 V rated value                                                                        | 6 A                                             |
| • at 400 V rated value                                                                        | 3 A                                             |
| <b>Operating current at DC-12</b>                                                             |                                                 |
| • at 60 V rated value                                                                         | 6 A                                             |
| • at 110 V rated value                                                                        | 3 A                                             |
| • at 220 V rated value                                                                        | 1 A                                             |
| <b>Operating current at DC-13</b>                                                             |                                                 |
| • at 24 V rated value                                                                         | 10 A                                            |
| • at 60 V rated value                                                                         | 2 A                                             |
| • at 110 V rated value                                                                        | 1 A                                             |
| • at 220 V rated value                                                                        | 0.3 A                                           |
| <b>Contact reliability of auxiliary contacts</b>                                              | 1 faulty switching per 100 million (17 V, 1 mA) |
| <b>Short-circuit protection</b>                                                               |                                                 |
| <b>Design of the fuse link</b>                                                                |                                                 |

- for short-circuit protection of the main circuit
  - with type of coordination 1 required
  - with type of assignment 2 required
- for short-circuit protection of the auxiliary switch required

fuse gL/gG: 63 A  
 fuse gL/gG: 25 A  
 fuse gL/gG: 10 A

## Installation/ mounting/ dimensions

|                                                                                      |                                                                                        |
|--------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| <b>Mounting type</b>                                                                 | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022 |
| • Side-by-side mounting                                                              | Yes                                                                                    |
| <b>Height</b>                                                                        | 85 mm                                                                                  |
| <b>Width</b>                                                                         | 45 mm                                                                                  |
| <b>Depth</b>                                                                         | 91 mm                                                                                  |
| <b>Required spacing</b>                                                              |                                                                                        |
| • for grounded parts <ul style="list-style-type: none"> <li>— at the side</li> </ul> | 6 mm                                                                                   |

## Connections/Terminals

|                                                                                                                                                                       |                                                                                                                                                                                                                                                                  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Type of electrical connection</b>                                                                                                                                  |                                                                                                                                                                                                                                                                  |
| • for main current circuit                                                                                                                                            | screw-type terminals                                                                                                                                                                                                                                             |
| • for auxiliary and control current circuit                                                                                                                           | screw-type terminals                                                                                                                                                                                                                                             |
| <b>Type of connectable conductor cross-sections</b>                                                                                                                   |                                                                                                                                                                                                                                                                  |
| • for main contacts <ul style="list-style-type: none"> <li>— solid</li> <li>— single or multi-stranded</li> <li>— finely stranded with core end processing</li> </ul> | 2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6 mm <sup>2</sup> ), max. 2x 10 mm <sup>2</sup><br>2x (1 ... 2,5 mm <sup>2</sup> ), 2x (2,5 ... 6 mm <sup>2</sup> ), max. 2x 10 mm <sup>2</sup><br>2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6 mm <sup>2</sup> ) |
| • at AWG conductors for main contacts                                                                                                                                 | 2x (16 ... 12), 2x (14 ... 10), 1x 8                                                                                                                                                                                                                             |
| <b>Type of connectable conductor cross-sections</b>                                                                                                                   |                                                                                                                                                                                                                                                                  |
| • for auxiliary contacts <ul style="list-style-type: none"> <li>— solid</li> <li>— finely stranded with core end processing</li> </ul>                                | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> ), max. 2x (0.75 ... 4 mm <sup>2</sup> )<br>2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )                                                                            |
| • at AWG conductors for auxiliary contacts                                                                                                                            | 2x (20 ... 16), 2x (18 ... 14), 1x 12                                                                                                                                                                                                                            |

## Certificates/approvals

| General Product Approval                                                                 |                                                                                          |                                                                                   | Declaration of Conformity                                                                     | Test Certificates                                 |                                               |
|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|---------------------------------------------------|-----------------------------------------------|
| <br>CCC | <br>CSA |  | <br>EG-Konf. | <a href="#">Typprüfbescheinigung/Werkszeugnis</a> | <a href="#">spezielle Prüfbescheinigungen</a> |

| Shipping Approval                                                                        |                                                                                          |                                                                                         |                                                                                          |                                                                                             |                                                                                             |
|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| <br>ABS | <br>DNV | <br>GL | <br>LRS | <br>RINA | <br>RMRS |

| other                             |                               |                         |
|-----------------------------------|-------------------------------|-------------------------|
| <a href="#">Umweltbestätigung</a> | <a href="#">Bestätigungen</a> | <a href="#">sonstig</a> |

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT1024-1AG20-Z W96>

##### Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT1024-1AG20-Z W96>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT1024-1AG20-Z W96>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT1024-1AG20-Z W96&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT1024-1AG20-Z W96&lang=en)



last modified:

10/17/2016