



CONTACTOR,  
110KW/400V/AC-3 AC(40...60HZ)/DC OPERATION UC 96-  
127V AUXILIARY CONTACTS 2NO+2NC 3-POLE,  
SIZE S10 BAR CONNECTIONS ELECTRONIC  
OPERATING MECHANISM WITH 24 V DC PLC  
INTERFACE CAGE CLAMP TERMINAL

| General technical data:                                                               |    |             |
|---------------------------------------------------------------------------------------|----|-------------|
| product brand name                                                                    |    | SIRIUS      |
| Size of the contactor                                                                 |    | S10         |
| Protection class IP / on the front                                                    |    | IP00        |
| Degree of pollution                                                                   |    | 3           |
| Installation altitude / at a height over sea level / maximum                          | m  | 2,000       |
| Ambient temperature / during operating                                                | °C | -25 ... +60 |
| Mechanical operating cycles as operating time                                         |    |             |
| • of the contactor / typical                                                          |    | 10,000,000  |
| • of the contactor with added auxiliary switch block / typical                        |    | 10,000,000  |
| • of the contactor with added electronics-compatible auxiliary switch block / typical |    | 5,000,000   |

| Main circuit:                                |   |     |
|----------------------------------------------|---|-----|
| Number of NC contacts / for main contacts    |   | 0   |
| Number of NO contacts / for main contacts    |   | 3   |
| Operating current                            |   |     |
| • at AC-1 / at 400 V                         |   |     |
| • at 40 °C ambient temperature / rated value | A | 275 |
| • at AC-3 / at 400 V / rated value           | A | 225 |
| • at AC-4 / at 400 V / rated value           | A | 195 |

|                                                      |    |         |
|------------------------------------------------------|----|---------|
| • with 1 current path / at DC-1                      |    |         |
| • at 24 V / rated value                              | A  | 200     |
| • at 110 V / rated value                             | A  | 18      |
| • with 2 current paths in series / at DC-1           |    |         |
| • at 24 V / rated value                              | A  | 200     |
| • at 110 V / rated value                             | A  | 200     |
| • with 3 current paths in series / at DC-1           |    |         |
| • at 24 V / rated value                              | A  | 200     |
| • at 110 V / rated value                             | A  | 200     |
| • with 1 current path / at DC-3 / at DC-5            |    |         |
| • at 24 V / rated value                              | A  | 200     |
| • at 110 V / rated value                             | A  | 2.5     |
| • with 2 current paths in series / at DC-3 / at DC-5 |    |         |
| • at 24 V / rated value                              | A  | 200     |
| • at 110 V / rated value                             | A  | 200     |
| • with 3 current paths in series / at DC-3 / at DC-5 |    |         |
| • at 24 V / rated value                              | A  | 200     |
| • at 110 V / rated value                             | A  | 200     |
| <b>Service power</b>                                 |    |         |
| • at AC-2 / at 400 V / rated value                   | kW | 128     |
| • at AC-3 / at 400 V / rated value                   | kW | 128     |
| • at AC-4 / at 400 V / rated value                   | W  | 110,000 |

| Control circuit:                                                                      |     |               |
|---------------------------------------------------------------------------------------|-----|---------------|
| <b>Design of the surge suppressor</b>                                                 |     | with varistor |
| <b>Voltage type / of control feed voltage</b>                                         |     | AC/DC         |
| <b>Operating range factor control supply voltage rated value / of the magnet coil</b> |     |               |
| • at 50 Hz                                                                            |     |               |
| • for AC                                                                              |     | 0.8 ... 1.1   |
| • at 60 Hz                                                                            |     |               |
| • for AC                                                                              |     | 0.8 ... 1.1   |
| • for DC                                                                              |     | 0.8 ... 1.1   |
| <b>Apparent pull-in power / of the solenoid / for AC</b>                              | V·A | 530           |
| <b>Apparent holding power / of the solenoid / for AC</b>                              | V·A | 5             |
| <b>Inductive power factor / with the pull-in power of the coil</b>                    |     | 0.8           |
| <b>Inductive power factor / with the pull-in power of the coil</b>                    |     | 0.4           |
| <b>Pull-in power / of the solenoid / for DC</b>                                       | W   | 580           |
| <b>Holding power / of the solenoid / for DC</b>                                       | W   | 3.8           |

| Auxiliary circuit: |  |  |
|--------------------|--|--|
|--------------------|--|--|

|                                                                                 |  |   |
|---------------------------------------------------------------------------------|--|---|
| <b>Number of NC contacts / for auxiliary contacts / instantaneous switching</b> |  | 2 |
| <b>Number of NO contacts / for auxiliary contacts / instantaneous switching</b> |  | 2 |

#### Short-circuit:

##### Design of the fuse link

- for short-circuit protection of the auxiliary switch / required
- for short-circuit protection of the main circuit
  - with type of assignment 1 / required
  - at type of coordination 2 / required

fuse gL/gG: 10 A

fuse gL/gG: 500 A

fuse gL/gG: 400 A

#### Installation/mounting/dimensions:

|                                                               |    |              |
|---------------------------------------------------------------|----|--------------|
| <b>Mounting type</b>                                          |    | screw fixing |
| <b>series installation</b>                                    |    | Yes          |
| <b>Width</b>                                                  | mm | 145          |
| <b>Height</b>                                                 | mm | 210          |
| <b>Depth</b>                                                  | mm | 202          |
| <b>Distance, to be maintained, to earthed part / sideways</b> | mm | 10           |

#### Connection type:

##### Design of the electrical connection

- for main current circuit
- for auxiliary and control current circuit

Cage Clamp terminals

Cage Clamp terminals

##### Type of the connectable conductor cross-section

- for AWG conductors / for main contacts
- for auxiliary contacts
  - solid
  - finely stranded
    - with conductor end processing
    - without conductor final cutting
- for AWG conductors / for auxiliary contacts

2/0 ... 500 kcmil

2x (0.25 ... 2.5 mm<sup>2</sup>)



2x (0.25 ... 1.5 mm<sup>2</sup>)

2x (0.25 ... 2.5 mm<sup>2</sup>)

2x (24 ... 14)

#### Certificates/approvals:

|                                                                                                                                                                                                                                                                  |                                                                                          |                                                                                          |                                                                                         |                                                                                                                                     |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| General Product Approval                                                                                                                                                                                                                                         |                                                                                          |                                                                                          | Functional Safety /<br>Safety of<br>Machinery                                           | Declaration of<br>Conformity                                                                                                        |
| <br>CCC                                                                                                                                                                         | <br>CSA |         | <br>UL | <a href="#">Type Examination</a><br><br>EG-Konf. |
| Test Certificates                                                                                                                                                                                                                                                | Shipping Approval                                                                        |                                                                                          |                                                                                         |                                                                                                                                     |
| <a href="#">Special Test<br/>Certificate</a>                                                                                                                                                                                                                     | <br>ABS | <br>DNV | <br>GL | <br>RMRS                                         |
| other                                                                                                                                                                                                                                                            |                                                                                          |                                                                                          |                                                                                         |                                                                                                                                     |
| <a href="#">Confirmation</a>                                                                                                                                                                                                                                     | <a href="#">other</a>                                                                    | <a href="#">Environmental<br/>Confirmations</a>                                          |                                                                                         |                                                                                                                                     |
| Further information:                                                                                                                                                                                                                                             |                                                                                          |                                                                                          |                                                                                         |                                                                                                                                     |
| Information- and Downloadcenter (Catalogs, Brochures,...)<br><a href="http://www.siemens.com/industrial-controls/catalogs">http://www.siemens.com/industrial-controls/catalogs</a>                                                                               |                                                                                          |                                                                                          |                                                                                         |                                                                                                                                     |
| Industry Mall (Online ordering system)<br><a href="http://www.siemens.com/industrial-controls/mall">http://www.siemens.com/industrial-controls/mall</a>                                                                                                          |                                                                                          |                                                                                          |                                                                                         |                                                                                                                                     |
| Cax online generator:<br><a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>                                                                                                                                                                     |                                                                                          |                                                                                          |                                                                                         |                                                                                                                                     |
| Service&Support (Manuals, Certificates, Characteristics, FAQs,...)<br><a href="http://support.automation.siemens.com/WW/view/en/3RT1064-2NF36/all">http://support.automation.siemens.com/WW/view/en/3RT1064-2NF36/all</a>                                        |                                                                                          |                                                                                          |                                                                                         |                                                                                                                                     |
| Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)<br><a href="http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RT1064-2NF36">http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RT1064-2NF36</a> |                                                                                          |                                                                                          |                                                                                         |                                                                                                                                     |



last change:

Jul 28, 2014