



ELECTRONIC TIME RELAY WITH SEMICONDUCTOR OUTPUT,
TIME RANGE 5...100S, 90...240 V AC/DC,
OFF DELAY,
W. VARISTOR FOR ATTACHING ON CONTACTORS,
SIZE S00

General technical data:		
product brand name		SIRIUS
Product designation		timing relay
Design of the product		off-delayed with auxiliary voltage
Type of voltage		AC
Size of the contactor / can be combined / company-specific		S00
Product function		
• star-delta circuit		No
• at the relay outputs / changeover delayed/without delay		No
Product component / semi-conductor output		Yes
Product extension / optional / remote control		No
Product extension / strictly required / remote control		No
Adjustable time	s	5 ... 100
Ambient temperature		
• during operating	°C	-25 ... +60
Reference code		
• according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		K
• according to DIN EN 61346-2		K

Switching Function:

Switching function		
• slow-operating		No
• making pulse contact		No
• firmly clocked beginning with pulse		No
• firmly clocked beginning with pause		No
• relapse delayed		Yes
• variably clocked start with impulse		No
• impuls variably clocked start with pause		No
• with control signal		
• additive ON delay		No
• passing break contact		No
• OFF delay		Yes
• without control signal / OFF delay		No

Auxiliary circuit:

Supply voltage frequency / for auxiliary and control current circuit

- rated value

Hz

50 ... 60

Supply voltage / strictly required / auxiliary voltage

Yes

Control supply voltage

- at 50 Hz / at AC
- rated value
- at 60 Hz / at AC
- rated value

V

90 ... 240

V

90 ... 240

Installation/mounting/dimensions:

Width

mm

45

Height

mm

38

Depth

mm

38

Connections:

Design of the electrical connection

- jumper socket
- for auxiliary and control current circuit

No

screw-type terminals

Certificates/approvals:

General Product Approval	EMC	Functional Safety / Safety of Machinery
--------------------------	-----	---



CCC



CSA



UL



C-TICK

[Type Examination](#)

Declaration of Conformity

Test Certificates



EG-Konf.

[Special Test Certificate](#)

Shipping Approval



ABS



BUREAU
VERITAS



DNV



GL



LRS



PRS

Shipping Approval

other



RINA



RMRS

[Confirmation](#)

[Declaration of Conformity](#)

[other](#)

[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator



<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RT1916-2DH31/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RT1916-2DH31



last change:

Jun 16, 2014