



SOLID-STATE,
TIME-DELAYED AUXILIARY SWITCH BLOCK SETTING
RANGE 5 S...100 S,
AC 200...240 V, 1NO + 1NC, ON-DELAY,
FOR MOUNTING ONTO CONTACTORS SIZE S0...S12

General technical data:		
product brand name		SIRIUS
Product designation		auxiliary switch
Design of the product		slow-operating
Type of voltage		AC
Size of the contactor / can be combined / company-specific		S0 ... S12
Product function		
• star-delta circuit		No
• at the relay outputs / changeover delayed/without delay		No
Product component / semi-conductor output		No
Product extension / optional / remote control		No
Product extension / strictly required / remote control		No
Adjustable time	s	5 ... 100
Ambient temperature		
• during operating	°C	-25 ... +60
Reference code		
• according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		K
• according to DIN EN 61346-2		K

Switching Function:

Switching function		
• slow-operating		Yes
• making pulse contact		No
• firmly clocked beginning with pulse		No
• firmly clocked beginning with pause		No
• relapse delayed		No
• variably clocked start with impulse		No
• impuls variably clocked start with pause		No
• with control signal		
• additive ON delay		No
• passing break contact		No
• OFF delay		No
• without control signal / OFF delay		No

Auxiliary circuit:

Number of NC contacts		
• delayed switching		1
Number of NO contacts		
• delayed switching		1
Supply voltage frequency / for auxiliary and control current circuit		
• rated value	Hz	50 ... 60
Supply voltage / strictly required / auxiliary voltage		No
Control supply voltage		
• at 50 Hz / at AC		
• rated value	V	200 ... 240
• at 60 Hz / at AC		
• rated value	V	200 ... 240

Installation/mounting/dimensions:

Width	mm	33
Height	mm	46
Depth	mm	73

Connections:

Design of the electrical connection		
• jumper socket		No
• for auxiliary and control current circuit		screw-type terminals

Certificates/approvals:

General Product Approval



CCC



CSA



UL

Functional Safety / Safety of Machinery

[Type Examination](#)

Declaration of Conformity



EG-Konf.

Test Certificates

[Special Test
Certificate](#)

Shipping Approval



ABS



BUREAU
VERITAS



DNV



GL



LRS



PRS

Shipping Approval

other



RINA



RMRS

[Confirmation](#)

[Declaration of
Conformity](#)

[other](#)

[Environmental
Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator


<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RT1926-2ED31/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RT1926-2ED31



last change:

Jun 16, 2014