

WITHDRAWABLE COIL FOR SIZE S10 FOR CONTACTORS
3RT106/3RT146 AC/DC OPERATION UC96-127V DRIVE:
ELECTRONIC WITH 24 V DC PLC INTERFACE CAGE CLAMP
CONNECTIONS



Figure similar

General technical data:	
product brand name	SIRIUS
Product designation	Magnet coil
Control circuit:	
Type of voltage of the control supply voltage	AC/DC
Control supply voltage	
• 1 at AC	
— at 50 Hz rated value	96 V
— at 60 Hz rated value	96 V
• 2 at AC	
— at 50 Hz rated value	127 V
— at 60 Hz rated value	127 V
Control supply voltage	
• 1 at DC rated value	96 V
• 2 at DC rated value	127 V
Certificates/ approvals:	

General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval
 CSA	 EAC	 EG-Konf.	spezielle Prüfbescheinigungen n  ABS  BUREAU VERITAS

Shipping Approval						
 DNV	 GL	 LRS	 PRS	 RINA	 RMRS	

other		
Bestätigungen	Umweltbestätigung	sonstig

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT1965-5NF32>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT1965-5NF32>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT1965-5NF32&lang=en

last modified:

10/07/2016