

WITHDRAWABLE COIL FOR SIZE S12 F. CONTS.
3RT107/3RT127/3RT147 AC/DC OPERATION UC200-277V DRIVE:
ELECTRONIC WITH 24 V DC PLC INTERFACE CAGE CLAMP
CONNECTIONS



Figure similar

General technical data:	
product brand name	SIRIUS
Product designation	Magnet coil
Control circuit:	
Type of voltage of the control supply voltage	AC/DC
Control supply voltage	
• 1 at AC	
— at 50 Hz rated value	200 V
— at 60 Hz rated value	200 V
• 2 at AC	
— at 50 Hz rated value	277 V
— at 60 Hz rated value	277 V
Control supply voltage	
• 1 at DC rated value	200 V
• 2 at DC rated value	277 V
Certificates/ approvals:	

General Product Approval			Declaration of Conformity	Test Certificates	
				spezielle Prüfbescheinigungen	Typprüfbescheinigung/Werkszeugnis
CSA	UL		EG-Konf.	n	

Shipping Approval					
					
ABS		DNV	GL	LRS	PRS

Shipping Approval	other		
		Bestätigungen	Umweltbestätigung
RINA	RMRS		sonstig

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT1975-5NP32>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT1975-5NP32>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT1975-5NP32&lang=en

last modified:

10/07/2016