



CONTACTOR, AC-3, 4KW/400V, 1NO+1NC,
DC 24V, 3-POLE, SZ S0 SCREW TERMINAL

General technical data:		
product brand name		SIRIUS
Size of the contactor		S0
Product extension		
• auxiliary switch		Yes
• function module for communication		No
Protection class IP / on the front		IP20
Protection against electrical shock		finger-safe
Degree of pollution		3
Installation altitude / at a height over sea level / maximum	m	2,000
Ambient temperature		
• during storage	°C	-55 ... +80
• during operating	°C	-25 ... +60
Shock resistance		
• at rectangular impulse		
• at DC		10g / 5 ms, 7,5g / 10 ms
• at sine pulse		
• at DC		15g / 5 ms, 10g / 10 ms
Impulse voltage resistance / rated value	kV	6
Insulation voltage / rated value	V	690

Maximum permissible voltage for protective separation / between coil and main contacts / in accordance with EN 60947-1	V	400
Mechanical operating cycles as operating time		
• of the contactor / typical		10,000,000
• of the contactor with added auxiliary switch block / typical		10,000,000
• of the contactor with added electronics-compatible auxiliary switch block / typical		5,000,000
Main circuit:		
Number of NC contacts / for main contacts		0
Number of NO contacts / for main contacts		3
Connectable conductor cross-section / in main circuit		
• at AC-1		
• at 40 °C / minimum permissible	mm ²	10
• at 60 °C / minimum permissible	mm ²	10
Operating current		
• at AC-1 / up to 690 V		
• at 40 °C ambient temperature / rated value	A	40
• at 60 °C ambient temperature / rated value	A	35
• at AC-2 / at 400 V / rated value	A	9
• at AC-3		
• at 400 V / rated value	A	9
• at 500 V / rated value	A	9
• at 690 V / rated value	A	9
• at AC-4 / at 400 V / rated value	A	8.5
Operational current / for ≥ 200000 operating cycles / at AC-4		
• at 400 V / rated value	A	4.1
• at 690 V / rated value	A	3.3
Operating current		
• with 1 current path / at DC-1		
• at 24 V / rated value	A	35
• at 110 V / rated value	A	4.5
• at 220 V / rated value	A	1
• at 440 V / rated value	A	0.4
• at 600 V / rated value	A	0.25
• with 2 current paths in series / at DC-1		
• at 24 V / rated value	A	35
• at 110 V / rated value	A	35
• at 220 V / rated value	A	5
• at 440 V / rated value	A	1
• at 600 V / rated value	A	0.8

• with 3 current paths in series / at DC-1 • at 24 V / rated value • at 110 V / rated value • at 220 V / rated value • at 440 V / rated value • at 600 V / rated value	A	35
	A	35
	A	35
	A	2.9
	A	1.4
Operating current		
• with 1 current path / at DC-3 / at DC-5 • at 24 V / rated value • at 110 V / rated value • at 220 V / rated value • at 440 V / rated value • at 600 V / rated value • with 2 current paths in series / at DC-3 / at DC-5 • at 24 V / rated value • at 110 V / rated value • at 220 V / rated value • at 440 V / rated value • at 600 V / rated value • with 3 current paths in series / at DC-3 / at DC-5 • at 24 V / rated value • at 110 V / rated value • at 220 V / rated value • at 440 V / rated value • at 600 V / rated value	A	20
	A	2.5
	A	1
	A	0.09
	A	0.06
	A	35
	A	15
	A	3
	A	0.27
	A	0.16
	A	35
	A	35
	A	10
	A	0.6
	A	0.6
Operating performance		
• at AC-1 / at 230 V / rated value • at AC-1 / at 400 V / rated value • at AC-1 / at 690 V / rated value • at AC-2 • at 400 V / rated value • at AC-3 • at 230 V / rated value • at 400 V / rated value • at 690 V / rated value • at AC-4 • at 400 V / rated value	kW	13.3
	kW	23
	kW	40
	kW	4
	kW	2.2
	kW	4
	kW	7.5
	kW	4
Operating performance / for ≥ 200000 operating cycles / at AC-4		
• at 400 V / rated value • at 690 V / rated value	kW	2
	kW	2.5

Thermal short-time current / restricted to 10 s	A	80
Active power loss / at AC-3 / at 400 V / with rated Operating current value / per conductor	W	0.4
Off-load operating frequency • at DC	1/h	1,500
Frequency of operation • with AC-1 / maximum • with AC-2 / maximum • with AC-3 / maximum • with AC-4 / maximum	1/h 1/h 1/h 1/h	1,000 1,000 1,000 300

Control circuit/ Control:		
Voltage type / of control feed voltage		DC
Control supply voltage • for DC / rated value	V	24
Operating range factor control supply voltage rated value / of the magnet coil • for DC		0.8 ... 1.1
Pull-in power / of the solenoid / for DC	W	5.9
Holding power / of the solenoid / for DC	W	5.9
Closing delay • at DC	ms	50 ... 170
Opening delay • at DC	ms	15 ... 17.5
Arcing time	ms	10 ... 10
Residual current / of electronics / for control with signal <0> • at 230 V / with AC / maximum permissible • at 24 V / with DC / maximum permissible	mA mA	6 16

Auxiliary circuit:		
Contact reliability / of the auxiliary contacts		1 faulty switching per 100 million (17 V, 1 mA)
Number of NC contacts / for auxiliary contacts / instantaneous switching		1
Number of NO contacts / for auxiliary contacts / instantaneous switching		1
Operating current • at AC-12 / maximum • at AC-15 • at 230 V / rated value • at 400 V / rated value • at 500 V / rated value • at 690 V / rated value	A A A A A	10 10 3 2 1

Operating current / at DC-12 • at 24 V / rated value • at 48 V / rated value • at 60 V / rated value • at 110 V / rated value • at 125 V / rated value • at 220 V / rated value • at 440 V / rated value • at 600 V / rated value	A	10
	A	6
	A	6
	A	3
	A	2
	A	1
	A	0.3
	A	0.15
Operating current / at DC-13 • at 24 V / rated value • at 48 V / rated value • at 60 V / rated value • at 110 V / rated value • at 125 V / rated value • at 220 V / rated value • at 440 V / rated value • at 600 V / rated value	A	10
	A	2
	A	2
	A	1
	A	0.9
	A	0.3
	A	0.14
	A	0.1

UL/CSA ratings:

yielded mechanical performance [hp] • for single-phase squirrel cage motors • at 110/120 V / rated value • at 230 V / rated value • for three-phase squirrel cage motors • at 200/208 V / rated value • at 220/230 V / rated value • at 460/480 V / rated value • at 575/600 V / rated value	hp	1
	hp	1
	hp	2
	hp	3
	hp	5
	hp	7.5
Full-load current (FLA) / for 3-phase motor • at 480 V / rated value • at 600 V / rated value	A	7.6
	A	9
Contact rating designation / for auxiliary contacts / according to UL		A600 / Q600

Short-circuit:

Design of the fuse link • for short-circuit protection of the auxiliary switch / required • for short-circuit protection of the main circuit • with type of assignment 1 / required	fuse gL/gG: 10 A	
	gL/gG LV HRC 3NA, DIAZED 5SB, NEOZED 5SE: 63 A	

- at type of coordination 2 / required

gL/gG LV HRC 3NA, DIAZED 5SB, NEOZED 5SE:
25A

Installation/ mounting/ dimensions:

mounting position		+/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface
Mounting type		screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
Mounting type / series installation		Yes
Width	mm	45
Height	mm	85
Depth	mm	107
Distance, to be maintained, to the ranks assembly / sideways	mm	0

Connections/ terminals:

Design of the electrical connection

- for main current circuit
- for auxiliary and control current circuit
- for main contacts / finely stranded / with conductor end
processing
- for AWG conductors / for main contacts
- for auxiliary contacts / finely stranded / with conductor end
processing
- for AWG conductors / for auxiliary contacts

screw-type terminals
screw-type terminals
2x (1 ... 2.5 mm²), 2x (2.5 ... 6 mm²), 1x 10 mm²

2x (16 ... 12), 2x (14 ... 8)
2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)





2x (20 ... 16), 2x (18 ... 14)

Safety related data:

B10 value / with high demand rate		
• according to SN 31920		1,000,000
T1 value / for proof test interval or service life		
• according to IEC 61508	a	20
Proportion of dangerous failures		
• with low demand rate / according to SN 31920	%	40
• with high demand rate / according to SN 31920	%	73
Failure rate [FIT] / with low demand rate		
• according to SN 31920	FIT	100
Product function		
• mirror contact to IEC 60947-4-1		Yes
• positively driven operation to IEC 60947-5-1		No

Certificates/ approvals:

General Product Approval			EMC	Functional Safety / Safety of Machinery	
 CCC	 CSA		 UL	 C-TICK	Type Examination
Declaration of Conformity	Test Certificates				
 EG-Konf.	Special Test Certificate	Type Test Certificates/Test Report			
Shipping Approval					
 ABS	 BUREAU VERITAS	 DNV	 GL	 LRS	 PRS
Shipping Approval		other			
 RINA	 RMRS	Confirmation		Environmental Confirmations	
 VDE					
Further information:					
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/industrial-controls/catalogs					
Industry Mall (Online ordering system) http://mall.industry.siemens.com/					
Cax online generator http://www.siemens.com/cax					
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/3RT2023-1BB40/all					
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RT2023-1BB40					



last change:

Aug 4, 2014