



2NO+2NC CONTACTOR,
AC3: 11KW AC 110V 50HZ 4-POLE, 2NO+2NC,
SZ: S0,
SPRING-LOADED TERMINAL 1NO+1NC INTEGR.

General technical data:

product brand name		SIRIUS
Size of the contactor		S0
Product extension		
• auxiliary switch		Yes
• function module for communication		No
Protection class IP / on the front		IP20
Protection against electrical shock		finger-safe
Degree of pollution		3
Installation altitude / at a height over sea level / maximum	m	2,000
Ambient temperature		
• during storage	°C	-55 ... +80
• during operating	°C	-25 ... +60
Shock resistance		
• at rectangular impulse		
• at AC		8,3g / 5 ms, 5,3g / 10 ms
• at sine pulse		
• at AC		13,5g / 5 ms, 8,3g / 10 ms
Impulse voltage resistance / rated value	kV	6
Insulation voltage / rated value	V	690

Maximum permissible voltage for protective separation / between coil and main contacts / in accordance with EN 60947-1	V	400
Mechanical operating cycles as operating time		
• of the contactor / typical		10,000,000
• of the contactor with added auxiliary switch block / typical		10,000,000
• of the contactor with added electronics-compatible auxiliary switch block / typical		5,000,000
Main circuit:		
Number of NC contacts / for main contacts		2
Number of NO contacts / for main contacts		2
Operational current / at AC-1 / up to 690 V		
• at 40 °C ambient temperature / rated value	A	40
• at 60 °C ambient temperature / rated value	A	35
Operating current / at AC-2 / at AC-3		
• at 400 V		
• per NO contact / rated value	A	25
• per NC contact / rated value	A	25
Operating current		
• with 1 current path / at DC-1		
• at 24 V / rated value	A	35
• at 110 V / rated value	A	4.5
• at 220 V / rated value	A	1
• at 440 V / rated value	A	0.4
• with 2 current paths in series / at DC-1		
• at 24 V / rated value	A	35
• at 110 V / rated value	A	35
• at 220 V / rated value	A	5
• at 440 V / rated value	A	1
Operating current		
• with 1 current path / at DC-3 / at DC-5		
• at 24 V		
• per NO contact / rated value	A	20
• per NC contact / rated value	A	20
• at 110 V		
• per NO contact / rated value	A	2.5
• per NC contact / rated value	A	1.25
• at 220 V		
• per NO contact / rated value	A	1
• per NC contact / rated value	A	0.5
• at 440 V		

• per NO contact / rated value	A	0.09
• per NC contact / rated value	A	0.045
• with 2 current paths in series / at DC-3 / at DC-5		
• at 24 V		
• per NO contact / rated value	A	35
• per NC contact / rated value	A	35
• at 110 V		
• per NO contact / rated value	A	15
• per NC contact / rated value	A	7.5
• at 220 V		
• per NO contact / rated value	A	3
• per NC contact / rated value	A	1.5
• at 440 V		
• per NO contact / rated value	A	0.27
• per NC contact / rated value	A	0.135
Operating performance		
• at AC-1		
• at 230 V / rated value	kW	15
• at 400 V / rated value	kW	26
• at AC-2 / at AC-3		
• at 230 V		
• per NO contact / rated value	kW	5.5
• per NC contact / rated value	kW	5.5
• at 400 V		
• per NO contact / rated value	kW	11
• per NC contact / rated value	kW	11
Active power loss / at AC-3 / at 400 V / with rated Operating current value / per conductor	W	1.6
Off-load operating frequency		
• at AC	1/h	5,000
• at DC	1/h	1,500
Frequency of operation		
• with AC-1 / maximum	1/h	1,000
• at AC-2 / at AC-3 / maximum	1/h	750
Control circuit/ Control:		
Voltage type / of control feed voltage		AC
Control supply voltage		
• at 50 Hz / at AC / rated value	V	110
operating range factor control supply voltage rated value / of the magnet coil		

• at 50 Hz / for AC		0.8 ... 1.1
• at 60 Hz / for AC		0.85 ... 1.1
Apparent pull-in power / of the solenoid / for AC	V·A	77
Apparent holding power / of the solenoid / for AC	V·A	9.8
Inductive power factor		
• with the pull-in power of the coil		0.82
• with the pull-in power of the coil		0.25
Closing delay		
• at AC	ms	8 ... 40
Opening delay		
• at AC	ms	4 ... 16
Arcing time	ms	10 ... 10
Residual current / of electronics / for control with signal <0>		
• at 230 V / with AC / maximum permissible	A	0.0070

Auxiliary circuit:		
Contact reliability / of the auxiliary contacts		1 faulty switching per 100 million (17 V, 1 mA)
Number of NC contacts / for auxiliary contacts / instantaneous switching		1
Number of NO contacts / for auxiliary contacts / instantaneous switching		1
Operating current		
• at AC-12 / maximum	A	10
• at AC-15 / at 230 V / rated value	A	10
• at AC-15 / at 400 V / rated value	A	3
• at AC-15 / at 500 V / rated value	A	2
• at AC-15 / at 690 V / rated value	A	1
Operating current / at DC-12		
• at 24 V / rated value	A	10
• at 48 V / rated value	A	6
• at 60 V / rated value	A	6
• at 110 V / rated value	A	3
• at 125 V / rated value	A	2
• at 220 V / rated value	A	1
• at 440 V / rated value	A	0.3
• at 600 V / rated value	A	0.15
Operating current / at DC-13		
• at 24 V / rated value	A	10
• at 48 V / rated value	A	2
• at 60 V / rated value	A	2
• at 110 V / rated value	A	1

- at 125 V / rated value
- at 220 V / rated value
- at 440 V / rated value
- at 600 V / rated value

A	0.9
A	0.3
A	0.14
A	0.1

UL/CSA ratings:

yielded mechanical performance [hp]

- for single-phase squirrel cage motors
 - at 110/120 V / rated value
 - at 230 V / rated value

hp	2
hp	3

Contact rating designation / for auxiliary contacts / according to UL

A600 / Q600

Short-circuit:

Design of the fuse link

- for short-circuit protection of the auxiliary switch / required
- for short-circuit protection of the main circuit
 - with type of assignment 1 / required
 - at type of coordination 2 / required

fuse gL/gG: 10 A

gL/gG LV HRC 3NA, DIAZED 5SB, NEOZED 5SE: 63 A

gL/gG LV HRC 3NA, DIAZED 5SB, NEOZED 5SE: 35 A

Installation/ mounting/ dimensions:

mounting position

+/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface

Mounting type

screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022

Mounting type / series installation

Yes

Width

mm 61

Height

mm 102

Depth

mm 97

Connections/ terminals:

Design of the electrical connection

- for main current circuit
- for auxiliary and control current circuit

spring-loaded terminals

spring-loaded terminals

Type of the connectable conductor cross-section

- for main contacts
 - solid
 - finely stranded
 - with conductor end processing
 - without conductor final cutting

2x (1 ... 10 mm²)

2x (1 ... 6 mm²)

2x (1 ... 6 mm²)

- for AWG conductors / for main contacts
- for auxiliary contacts
 - solid
 - finely stranded
 - with conductor end processing
 - without conductor final cutting
- for AWG conductors / for auxiliary contacts

2x (18 ... 8)

2x (0.5 ... 2.5 mm²)

2x (0.5 ... 1.5 mm²)

2x (0.5 ... 1.5 mm²)

2x (20 ... 14)

Safety related data:

B10 value / with high demand rate

- according to SN 31920

1,000,000

T1 value / for proof test interval or service life

- according to IEC 61508

a

20

Proportion of dangerous failures

- with low demand rate / according to SN 31920
- with high demand rate / according to SN 31920

%

40

%

73

Failure rate [FIT] / with low demand rate

- according to SN 31920

FIT

100

Product function




- mirror contact to IEC 60947-4-1
- positively driven operation to IEC 60947-5-1


Yes

No

Certificates/ approvals:

General Product Approval			EMC	Functional Safety / Safety of Machinery	
 CCC	 CSA		 UL	 C-TICK	Type Examination
Declaration of Conformity	Test Certificates				
 EG-Konf.	Special Test Certificate	Type Test Certificates/Test Report			
Shipping Approval					
 ABS	 BUREAU VERITAS	 DNV	 GL	 LRS	 PRS
Shipping Approval		other			
 RINA	 RMRS	Confirmation		 VDE	Environmental Confirmations
Further information:					
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/industrial-controls/catalogs					
Industry Mall (Online ordering system) http://www.siemens.com/industrymall					
Cax online generator http://www.siemens.com/cax					
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/3RT2526-2AF00/all					
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RT2526-2AF00					





last change:

Aug 4, 2014