

Additional load block, 50/60 Hz AC, 180 ... 255 V, for
contactor relays and motor contactors Size S00



General technical data:		
Product brand name		SIRIUS
Product designation		plug-in additional load module
Size of contactor		S00
Ambient temperature		
• during storage	°C	-40 ... +80
• during operation	°C	-25 ... +60
Control circuit/ Control:		
Type of voltage of the control supply voltage		AC
Control supply voltage frequency		
• 1 rated value	Hz	50
• 2 rated value	Hz	60
Control supply voltage 1		
• at AC		
— at 50 Hz Initial rated value	V	180
— at 50 Hz Final rated value	V	255
— at 60 Hz Final rated value	V	255
— at 60 Hz Initial rated value	V	180

Installation/ mounting/ dimensions:

Mounting position		any
Mounting type		clip-on
Width	mm	28
Height	mm	46
Depth	mm	9

Certificates/ approvals:

Certificate of suitability	CE / UL / CSA / CCC		
General Product Approval	EMC	Declaration of Conformity	Test Certificates
 UR		 RCM	 EG-Konf.
		Miscellaneous	Special Test Certificate

Shipping Approval	other
 BUREAU VERITAS	 PRS
 RINA	 RMRS
	Confirmation  VDE

Railway
Vibration and Shock

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2916-1GA00>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2916-1GA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2916-1GA00&lang=en





last modified:

07/25/2019