



magnetic coil 24 V AC, 50 Hz, for contactors 3RT2023-A, 3RT2024-A and 3RT2025-A

product brand name	SIRIUS
product category	Solenoid coils
product designation	Magnet coil
General technical data	
power loss [V·A] of magnet coil at AC typical	7.6 VA
Substance Prohibitance (Date)	10/01/2009
Weight	0.08 kg
type of voltage of the control supply voltage	AC
control supply voltage 1 at AC	
• at 50 Hz rated value	24 V
operating range factor control supply voltage rated value of magnet coil at AC	
• at 50 Hz	0.8 ... 1.1
apparent pick-up power of magnet coil at AC	
• at 50 Hz	65 VA
• at 60 Hz	73 VA
inductive power factor with closing power of the coil	
• at 50 Hz	0.82
• at 60 Hz	0.76
apparent holding power of magnet coil at AC	
• at 50 Hz	7.6 VA
• at 60 Hz	7.2 VA
inductive power factor with the holding power of the coil	
• at 50 Hz	0.25
• at 60 Hz	0.28

Approvals Certificates		
General Product Approval	EMV	Marine / Shipping



[Confirmation](#)



Marine / Shipping	other	Environment
-------------------	-------	-------------



[Miscellaneous](#)

[Confirmation](#)

[Environmental Con-
firmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2924-5AB01>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2924-5AB01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2924-5AB01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2924-5AB01&lang=en

last modified:

1/10/2024 