

MAGNET COIL F. CONTACTOR 18,5KW AC 48V, 50HZ FOR MOTOR CONTACTORS SZ S0, SCREW TERMINAL,

General technical data:

product brand name	SIRIUS
Product designation	Magnet coil

Control circuit:

Type of voltage of the control supply voltage	AC
Power loss [V·A] of magnet coil at AC typical	9.8 V·A
Control supply voltage <ul style="list-style-type: none"> <li>• 1 at AC                 <ul style="list-style-type: none"> <li>— at 50 Hz rated value</li> </ul> </li> </ul>	48 V
Operating range factor control supply voltage rated value of magnet coil at AC <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>	0.8 ... 1.1 0.85 ... 1.1

Certificates/ approvals:

General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval
--------------------------	---------------------------	-------------------	-------------------



[spezielle Prüfbescheinigung](#)  
n



Shipping Approval	other
-------------------	-------



[Bestätigungen](#)

[Umweltbestätigung](#)



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2926-5AH01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2926-5AH01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)  
[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2926-5AH01&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2926-5AH01&lang=en)

last modified:

10/07/2016