

MOTOR STARTER PROTECTOR S. S2,
FOR MOTOR PROTECTION, CLASS 20,
A-REL. 11...16A, N-REL.208A,
SCREW TERMINAL,
STANDARD SWITCHING CAPACITY REUSABLE
PACKAGING 1 PACK = 24 UNITS

General technical data:

product brand name		SIRIUS
product designation		circuit breaker
Size of the circuit-breaker		S2
Number of poles / for main current circuit		3
Product function - removable terminal for auxiliary and control circuit - overload protection - phase disturbance recognition - short-circuit to earth recognition		No Yes Yes No
Product component - auxiliary switch - undervoltage release mechanism - trip indicator		No No No
Product extension - auxiliary switch - optional / motor drive		Yes Yes
Impulse voltage resistance / rated value	V	6,000
Protection class IP / on the front		IP20
Protection against electrical shock		finger-safe
Installation altitude / at a height over sea level / maximum	m	2,000
Resistance against shock		25g / 11 ms
Ambient temperature - during transport - during storage - during operating	°C °C °C	-50 ... +80 -50 ... +80 -20 ... +70
Active power loss / total / typical	W	12

Main circuit:

Operating voltage / rated value	V	690
---------------------------------	---	-----

type of voltage		AC/DC
Service power / at AC-3 / at 400 V / rated value	kW	7.5
Operational current / at AC-3 / at 400 V / rated value	A	16
Mechanical operating cycles as operating time / of the main contacts / typical		50,000
Frequency of operation / at AC-3 / according to IEC 60947-6-2	1/h	15

Auxiliary circuit:

Number of change-over switches / for auxiliary contacts

0

Protection function:

Trip class

CLASS 20

Adjustable response current / of the current-dependent overload release

A

11 ... 16

Breaking capacity limit short-circuit current (I_{cu})

- at 400 V / rated value
- at 500 V / rated value
- at 690 V / rated value

kA

50

kA

12

kA

5

Installation/mounting/dimensions:

Type of mounting

screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022

mounting position

any

Depth

mm

149

Height

mm

140

Width

mm

55

Connections:

Arrangement of electrical connectors / for main current circuit

front side

Design of the electrical connection

- for main current circuit
- for auxiliary and control current circuit

screw-type terminals with box terminals

screw-type terminals

Type of the connectable conductor cross-section

- for main contacts
 - solid
 - finely stranded
 - with conductor end processing
 - stranded
- for AWG conductors / for main contacts

2x (0.75 ... 16 mm²)


2x (0.75 ... 16 mm²), 0.75 ... 25 mm²

2x (0.75 ... 25 mm²), 0.75 ... 35 mm²

2x (18 ... 2), 1x (18 ... 2)

Certificates/approvals:

General Product Approval			Declaration of Conformity	Test Certificates
				Special Test Certificate
CCC	GOST	UL	EG-Konf.	
Shipping Approval				
				
ABS	BUREAU VERITAS	DNV	RMRS	
other				
Confirmation	Declaration of Conformity	other	Environmental Confirmations	
Further information:				
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/industrial-controls/catalogs				
Industry Mall (Online ordering system) http://www.siemens.com/industrial-controls/mall				
Cax online generator: http://www.siemens.com/cax				
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/3RV1031-4AB10-ZX95/all				
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RV1031-4AB10-ZX95				



last change:

Feb 11, 2013