

3-PHASE LINE-SIDE TERMINAL,
F. 3-PHASE BUSBAR, CONNECTION FROM ABOVE

General technical data:

product brand name		SIRIUS
product designation		3-phase infeed terminal, size S2
Size of the circuit-breaker		S2
Protection class IP / on the front		IP20
Insulation voltage / with degree of pollution 3		
• rated value	V	690
Ambient temperature		
• during storage	°C	-50 ... +80
• during operating	°C	-20 ... +60
Current-carrying capacity / maximum	A	108

Installation/mounting/dimensions:

Width	mm	54
Height	mm	59
Depth	mm	44
Acceptability for application / makes the assembly of self-protected combination motor controllers (type E) according to UL 508 possible		No

Connections:

Design of the electrical connection		screw-type terminals
• for main current circuit		
Type of the connectable conductor cross-section		
• for main contacts		
• solid		1x (10 ... 50 mm²)
• stranded		1x (10 ... 50 mm²)
• for AWG conductors / for main contacts		1x (8 ... 0)

Certificates/approvals:

Verification of suitability		CE / UL / CSA / CCC
-----------------------------	--	---------------------

General Product Approval		Declaration of Conformity	Test Certificates	Shipping Approval	
 CSA	 UL	 EG-Konf.	Special Test Certificate	 BUREAU VERITAS	 RMRS

other

[Confirmation](#)

[Declaration of
Conformity](#)

[other](#)

[Special Test
Certificate](#)

[Environmental
Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:


<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RV1935-5A/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RV1935-5A



last change:

Jan 21, 2013