

REM. CONT. F. MOTOR SZ S2, DC 24V



General technical data:		
product brand name		SIRIUS
Product designation		Motor remote operating mechanism
Size of the circuit-breaker		S2
Design of the product		standard
Control version of the switch operating mechanism		Motor
Suitability for use		circuit-breakers S2
Ambient temperature		
• during storage	°C	-50 ... +80
• during operation	°C	-20 ... +70
Shock resistance		25g / 11 ms
Operating frequency maximum	1/h	25
Color of the actuating element		black
Control circuit/ Control:		
Type of voltage of the control supply voltage		DC
Control supply voltage		
• 1		
— at DC		

- rated value
- Initial rated value
- Final rated value

V	24
V	20.4
V	26.4

Installation/ mounting/ dimensions:

Mounting position		any
Mounting type		screw fixing
Width	mm	148
Height	mm	224
Depth	mm	211
Required spacing for grounded parts		
• forwards	mm	0
• Backwards	mm	0
• upwards	mm	0
• at the side	mm	0
• downwards	mm	0

Certificates/ approvals:

Certificate of suitability

CE

Declaration of
Conformity

Test
Certificates

Shipping Approval

other



EG-Konf.

[spezielle
Prüfbescheinigung](#)
[n](#)



[Umweltbestätigung](#)

[Bestätigungen](#)

other



VDE

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV1936-3AB4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RV1936-3AB4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV1936-3AB4&lang=en

last modified:

10/07/2016