



CIRCUIT-BREAKER SZ S0,
FOR PLANT PROTECTION,
WITH APPROBATION CIRCUIT-BREAKER UL 489. CSA
C22.2 NO.5-02. A-RELEASE 20 A,
N-RELEASE 260 A, SCREW CONNECTION,
STANDARD SW. CAPACITY

General technical data:

product brand name		SIRIUS
Product designation		3RV2 circuit breaker
Size of the circuit-breaker		S0
Number of poles / for main current circuit		3
Product function		
• short circuit protection		Yes
• overload protection		Yes
• phase disturbance recognition		No
• plant protection		Yes
• motor protection		Yes
• motor protection with relais overload functionality		No
• starter protection		No
• transformer protection		No
• disconnecter functionality		Yes
• main control switches with supply disconnect function and EM-STOP switches		No
Design of the operating mechanism		selector switch
Product component		
• auxiliary switch		No
• undervoltage release mechanism		No

• trip indicator		No
Product extension		
• auxiliary switch		Yes
• optional / motor drive		No
Insulation voltage / with degree of pollution 3 / rated value	V	690
Impulse voltage resistance / rated value	kV	6
Protection class IP		
• of the terminal		IP20
• on the front		IP20
Protection against electrical shock		finger-safe
Installation altitude / at a height over sea level / maximum	m	2,000
Relative humidity		
• during operating phase	%	10 ... 95
Ambient temperature		
• during transport	°C	-50 ... +80
• during storage	°C	-50 ... +80
• during operating	°C	-20 ... +60
Shock resistance / according to IEC 60068-2-27		25g / 11 ms
Usage category		
• according to IEC 60947-4-1		AC-3
Active power loss / total / typical	W	9.6

Main circuit:		
Operating voltage / rated value	V	690
Voltage type / for main circuit		AC/DC
Operating frequency		
• rated value	Hz	50 ... 60

Protective and monitoring functions:		
Verification of suitability / ATEX		No
Design of the overload circuit breaker		thermal
Adjustable response current / of the current-dependent overload release	A	14 ... 20
Design of the short-circuit trip		magnetic
Operational short-circuit current breaking capacity (Ics) / with AC		
• at 240 V / rated value	kA	100
• at 400 V / rated value	kA	25
• at 500 V / rated value	kA	5
• at 690 V / rated value	kA	2
Breaking capacity maximum short-circuit current (Icu)		

• at 240 V / for AC / rated value • at 400 V / for AC / rated value • at 500 V / for AC / rated value • at 690 V / for AC / rated value	kA	100
	kA	55
	kA	10
	kA	4
Design of fuse insert / for IT network / for short-circuit protection of the main circuit • at 400 V • at 500 V • at 690 V		gL/gG 63 A gL/gG 50 A gL/gG 50 A
Breaking capacity short-circuit current (I_{cn}) • with 1 current path / at 150 V / for DC / rated value • with 2 current paths in series / at 300 V / for DC / rated value • with 3 current paths in series / at 450 V / for DC / rated value	kA	10
	kA	10
	kA	10

Installation/ mounting/ dimensions:

Mounting type		screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 60715
mounting position		any
Depth	mm	97
Height	mm	144
Width	mm	45

Connections/ terminals:




Arrangement of electrical connectors / for main current circuit		Top and bottom
Design of the electrical connection / for main current circuit		screw-type terminals
Type of the connectable conductor cross-section • for main contacts • solid or multi-stranded • finely stranded • with conductor end processing • for AWG conductors / for main contacts		1 ... 10 mm ² , max. 2x 10 mm ² 1 ... 16 mm ² , max. 6 + 16 mm ² 2x 12

UL/CSA ratings:

Operating voltage / according to UL 60947 / rated value	V	600
Breaking capacity limit short-circuit current (I_{cu}) / at 480 AC Y/277 V / according to UL 489 / rated value	A	50,000

Certificates/ approvals:

General Product Approval			Declaration of Conformity	Test Certificates	
 CSA		 UL	 EG-Konf.	Special Test Certificate	Type Test Certificates/Test Report
Shipping Approval					
 ABS	 BUREAU VERITAS	 GL	 LRS	 RMRS	
other					
Confirmation	other	Environmental Confirmations			
Further information:					
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/industrial-controls/catalogs					
Industry Mall (Online ordering system) http://www.siemens.com/industrymall					
Cax online generator http://www.siemens.com/cax					
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/3RV2721-4BD10/all					
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RV2721-4BD10					



last change:

Aug 4, 2014