



VOLTAGE RELEASE, AC 20...24V, 50/60HZ,
100% ED, AC 20...70V, 50/60HZ, 5SEC ED,
DC 20...70V, 5SEC ED,
WITH SPRING-L. CONNECTION,
FOR CIRCUIT-BREAKERS, SZ S00/S0

General technical data:

product brand name		SIRIUS
Product designation		shunt release
Size of the circuit-breaker		S00, S0
Acceptability for application		motor circuit breaker
Protection class IP / on the front		IP20
Design of the short-circuit protection		fuse
Degree of pollution		3
Insulation voltage / rated value	V	690
Insulation voltage / with degree of pollution 3 / rated value	V	690
Ambient temperature		
• during storage	°C	-50 ... +80
• during operating	°C	-20 ... +60
Reference code		
• according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		F
• according to DIN EN 61346-2		F

Auxiliary circuit:

Number of NC contacts / for auxiliary contacts		
• instantaneous switching		0

Number of NO contacts / for auxiliary contacts • instantaneous switching		0
Number of NO contacts / for auxiliary contacts • leading switching		0
Number of changeover contacts / of the auxiliary contacts • instantaneous switching		0

Control circuit:

Voltage type / of control feed voltage		AC
Control supply voltage frequency • 1 / initial rated value • 1 / final rated value	Hz Hz	50 60
Control supply voltage • 1 / at 50 Hz / for AC / initial rated value • 1 / at 50 Hz / for AC / final rated value • 1 / at 60 Hz / for AC / final rated value • 1 / at 60 Hz / for AC / initial rated value	V V V V	20 24 24 20

Installation/mounting/dimensions:

Mounting type		snap-on mounting
Width	mm	18.5
Height	mm	90
Depth	mm	68

Certificates/approvals:

Verification of suitability	CE / UL / CSA
------------------------------------	---------------

General Product Approval

Declaration of Conformity

Test Certificates



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

Shipping Approval



Shipping Approval


other




[other](#)

[Environmental Confirmations](#)

Further information:





last change:

Jun 16, 2014