## **SIEMENS**

Product data sheet 3RV2922-1CB0

UNDERVOLTAGE RELEASE AC 24 V, 50 HZ, W. LEADING AUX. SWITCHES, 2NO, FOR CIRCUIT-BREAKER, SIZE S0...S3

| product brand name product designation Size of the circuit-breaker Design of the product         |    | SIRIUS undervoltage release |  |
|--|----|-----------------------------|--|
| Size of the circuit-breaker  |    |                             |  |
|  |    |                             |  |
| Design of the product  |    | S00, S0                     |  |
|  |    | with 2 auxiliary contacts   |  |
| Acceptability for application  |    | motor circuit breaker       |  |
| Protection class IP / on the front   |    | IP20                        |  |
| Design of the short-circuit protection   |    | fuse                        |  |
| Degree of pollution  |    | 3                           |  |
| Insulation voltage / rated value   | V  | 690                         |  |
| Insulation voltage / with degree of pollution 3 / rated value                                    | V  | 690                         |  |
| Ambient temperature  |    |                             |  |
| during storage   | °C | -50 +80                     |  |
| during operating   | °C | -20 +60                     |  |
| Item designation   |    |                             |  |
| <ul> <li>according to DIN 40719 extendable after IEC 204-2 / according<br/>to IEC 750</li> </ul> |    | F                           |  |
| according to DIN EN 61346-2  |    | F                           |  |
| Auxiliary circuit:   |    |                             |  |
| Number of NC contacts / for auxiliary contacts   |    |                             |  |
| instantaneous switching  |    | 0                           |  |
| Number of NO contacts / for auxiliary contacts   |    |                             |  |
| instantaneous switching  |    | 0                           |  |
| Number of NO contacts / for auxiliary contacts   |    |                             |  |
| leading switching  |    | 2                           |  |
| Number of changeover contacts / of the auxiliary contacts  |    |                             |  |
| • instantaneous switching  |    | 0                           |  |
| Control circuit:   |    |                             |  |
| Type of voltage / of the controlled supply voltage   |    | AC                          |  |
| Control supply voltage frequency   |    |                             |  |

• 1 / initial rated value

Hz

## Control supply voltage • 1 / at 50 Hz / for AC / rated value V 24

| Installation/mounting/dimensions: |    |                  |  |
|-----------------------------------|----|------------------|--|
| Type of mounting                  |    | snap-on mounting |  |
| Width                             | mm | 18.5             |  |
| Height                            | mm | 90               |  |
| Depth                             | mm | 68               |  |

## Certificates/approvals:

Verification of suitability CE / UL / CSA

Declaration of Conformity

**Test Certificates** 



Type Test
Certificates/Test
Report

## **Further information:**

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrial-controls/mall

**CAx-Online-Generator** 

http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/3RV2922-1CB0/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

 $\underline{\text{http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=3RV2922-1CB0}$ 

last change: Dec 17, 2012