



SIRIUS SOFT STARTER, VALUES WITH 460 V,  
50 DEG., STANDARD: 117A, 75HP,  
INSIDE-DELTA CIRCUIT 3: 203A, 150HP,  
200-460 V AC, 115 V AC,  
CAGE CLAMP TERMINALS

### General details:

|                                                                            |  |        |
|----------------------------------------------------------------------------|--|--------|
| <b>product brand name</b>                                                  |  | SIRIUS |
| <b>Product equipment</b>                                                   |  |        |
| • integrated bridging contact system                                       |  | Yes    |
| • thyristors                                                               |  | Yes    |
| <b>Product function</b>                                                    |  |        |
| • intrinsic device protection                                              |  | Yes    |
| • motor overload protection                                                |  | Yes    |
| • evaluation of thermal resistor motor protection                          |  | Yes    |
| • reset external                                                           |  | Yes    |
| • adjustable current limitation                                            |  | Yes    |
| • inside-delta circuit                                                     |  | Yes    |
| <b>Product component / outlet for enine brake</b>                          |  | Yes    |
| <b>Item designation</b>                                                    |  |        |
| • according to DIN EN 61346-2                                              |  | Q      |
| • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 |  | G      |

### Power Electronics:

|                            |  |                                             |
|----------------------------|--|---------------------------------------------|
| <b>product designation</b> |  | soft starters for high feature applications |
| Operating current          |  |                                             |

|                                                                                                                                                 |    |             |
|-------------------------------------------------------------------------------------------------------------------------------------------------|----|-------------|
| • at 40 °C / rated value                                                                                                                        | A  | 134         |
| • at 50 °C / rated value                                                                                                                        | A  | 117         |
| • at 60 °C / rated value                                                                                                                        | A  | 100         |
| • for three-phase servomotors / at 3-phase root switching                                                                                       |    |             |
| • at 40 °C / rated value                                                                                                                        | A  | 232         |
| • at 50 °C / rated value                                                                                                                        | A  | 203         |
| • at 60 °C / rated value                                                                                                                        | A  | 173         |
| <b>Emitted mechanical power / for three-phase servomotors</b>                                                                                   |    |             |
| • at 230 V / at standard switching / at 40 °C                                                                                                   |    |             |
| • rated value                                                                                                                                   | W  | 37,000      |
| • at 400 V / at standard switching / at 40 °C                                                                                                   |    |             |
| • rated value                                                                                                                                   | W  | 75,000      |
| • at 230 V / at 3-phase root switching / at 40 °C                                                                                               |    |             |
| • rated value                                                                                                                                   | W  | 75,000      |
| • at 400 V / at 3-phase root switching / at 40 °C                                                                                               |    |             |
| • rated value                                                                                                                                   | W  | 132,000     |
| <b>yielded mechanical performance (hp) / for three-phase squirrel cage motors / at 200/208 V / at standard circuit / at 50 °C / rated value</b> | hp | 30          |
| <b>Operating frequency</b>                                                                                                                      |    |             |
| • rated value                                                                                                                                   | Hz | 50 ... 60   |
| <b>Relative negative tolerance / of the operating frequency</b>                                                                                 | %  | -10         |
| <b>Relative positive tolerance / of the operating frequency</b>                                                                                 | %  | 10          |
| <b>Operating voltage / with standard circuit / rated value</b>                                                                                  | V  | 200 ... 460 |
| <b>Relative negative tolerance / of the operating voltage / with standard circuit</b>                                                           | %  | -15         |
| <b>Relative positive tolerance / of the operating voltage / with standard circuit</b>                                                           | %  | 10          |
| <b>Operating voltage / at 3-phase root switching / rated value</b>                                                                              | V  | 200 ... 460 |
| <b>Relative negative tolerance / of the operating voltage / with inside-delta circuit</b>                                                       | %  | -15         |
| <b>Relative positive tolerance / of the operating voltage / with inside-delta circuit</b>                                                       | %  | 10          |
| <b>Minimum load in % of I<sub>M</sub></b>                                                                                                       | %  | 8           |
| <b>Adjustable rated current / of the motor / for motor overload protection / minimum</b>                                                        | A  | 26          |
| <b>Continuous operating current in % of I<sub>e</sub> / at 40°C</b>                                                                             | %  | 115         |
| <b>Active power loss / at operating current / at 40°C / during operating phase / typical</b>                                                    | W  | 76          |
| <b>Control electronics:</b>                                                                                                                     |    |             |
| <b>Type of voltage / of the controlled supply voltage</b>                                                                                       |    | AC          |

|                                                                                 |    |         |
|---------------------------------------------------------------------------------|----|---------|
| Control supply voltage frequency / 1 / rated value                              | Hz | 50      |
| Control supply voltage frequency / 2 / rated value                              | Hz | 60      |
| Relative negative tolerance / of the control supply voltage frequency           | %  | -10     |
| Relative positive tolerance / of the control supply voltage frequency           | %  | 10      |
| Control supply voltage / 1                                                      |    |         |
| • at 50 Hz / for AC                                                             | V  | 115     |
| • at 60 Hz / for AC                                                             | V  | 115     |
| Relative negative tolerance / of the control supply voltage / at 60 Hz / for AC | %  | -15     |
| Relative positive tolerance / of the control supply voltage / at 60 Hz / for AC | %  | 10      |
| Type of display / for fault signal                                              |    | Display |

|                                                    |    |                                                                                                                   |
|----------------------------------------------------|----|-------------------------------------------------------------------------------------------------------------------|
| <b>Mechanical design:</b>                          |    |                                                                                                                   |
| Width                                              | mm | 170                                                                                                               |
| Height                                             | mm | 200                                                                                                               |
| Depth                                              | mm | 270                                                                                                               |
| Type of mounting                                   |    | screw fixing                                                                                                      |
| mounting position                                  |    | bei senkrechter Montageebene +/-90° drehbar, bei senkrechter Montageebene +/- 22,5° nach vorne und hinten kippbar |
| Distance, to be maintained, to the ranks assembly  |    |                                                                                                                   |
| • upwards                                          | mm | 100                                                                                                               |
| • sideways                                         | mm | 5                                                                                                                 |
| • downwards                                        | mm | 75                                                                                                                |
| Installation altitude / at a height over sea level | m  | 5,000                                                                                                             |
| Cable length / maximum                             | m  | 500                                                                                                               |
| Number of poles / for main current circuit         |    | 3                                                                                                                 |

|                                                                                                                              |  |                         |
|------------------------------------------------------------------------------------------------------------------------------|--|-------------------------|
| <b>Electrical connections:</b>                                                                                               |  |                         |
| Design of the electrical connection                                                                                          |  |                         |
| • for main current circuit                                                                                                   |  | busbar connection       |
| • for auxiliary and control current circuit                                                                                  |  | spring-loaded terminals |
| Number of NC contacts / for auxiliary contacts                                                                               |  | 0                       |
| Number of NO contacts / for auxiliary contacts                                                                               |  | 3                       |
| Number of change-over switches / for auxiliary contacts                                                                      |  | 1                       |
| Type of the connectable conductor cross-section / for main contacts / for box terminal / when using the front clamping point |  |                         |
| • finely stranded / with conductor end processing                                                                            |  | 16 ... 70 mm²           |
| • finely stranded / without conductor end processing                                                                         |  | 16 ... 70 mm²           |
| • stranded                                                                                                                   |  | 16 ... 70 mm²           |

|                                                                                                                                                                                                                                                                                                                                    |  |                                                                                                                                        |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>Type of the connectable conductor cross-section / for main contacts / for box terminal / when using the back clamping point</b> <ul style="list-style-type: none"> <li>finely stranded / with conductor end processing</li> <li>without conductor final cutting / without conductor end processing</li> <li>stranded</li> </ul> |  | 16 ... 70 mm <sup>2</sup><br>16 ... 70 mm <sup>2</sup><br>16 ... 70 mm <sup>2</sup>                                                    |
| <b>Type of the connectable conductor cross-section / for main contacts / for box terminal / when using both clamping points</b> <ul style="list-style-type: none"> <li>finely stranded / with conductor end processing</li> <li>without conductor final cutting / without conductor end processing</li> <li>stranded</li> </ul>    |  | max. 1x 50 mm <sup>2</sup> , 1x 70 mm <sup>2</sup><br>max. 1x 50 mm <sup>2</sup> , 1x 70 mm <sup>2</sup><br>max. 2x 70 mm <sup>2</sup> |
| <b>Type of the connectable conductor cross-section / for AWG conductors / for main contacts / for box terminal</b> <ul style="list-style-type: none"> <li>when using the back cl</li> <li>when using the front c</li> <li>when using both clampi</li> </ul>                                                                        |  | 6 ... 2/0<br>6 ... 2/0<br>max. 2x 1/0                                                                                                  |
| <b>Type of the connectable conductor cross-section / for DIN cable lug / for main contacts</b> <ul style="list-style-type: none"> <li>finely stranded</li> <li>stranded</li> </ul>                                                                                                                                                 |  | 16 ... 95 mm <sup>2</sup><br>25 ... 120 mm <sup>2</sup>                                                                                |
| <b>Type of the connectable conductor cross-section</b> <ul style="list-style-type: none"> <li>for AWG conductors / for main contacts</li> </ul>                                                                                                                                                                                    |  | 4 ... 250 kcmil                                                                                                                        |
| <b>Type of the connectable conductor cross-section</b> <ul style="list-style-type: none"> <li>for auxiliary contacts <ul style="list-style-type: none"> <li>solid</li> <li>finely stranded / with conductor end processing</li> </ul> </li> <li>for AWG conductors / for auxiliary contacts</li> </ul>                             |  | 2x (0.25 ... 1.5 mm <sup>2</sup> )<br>2x (0.25 ... 1.5 mm <sup>2</sup> )<br>2x (24 ... 16)                                             |

#### Ambient conditions:

|                                                                                                                       |            |                   |
|-----------------------------------------------------------------------------------------------------------------------|------------|-------------------|
| <b>Ambient temperature</b> <ul style="list-style-type: none"> <li>during operating</li> <li>during storage</li> </ul> | / °C<br>°C | 60<br>-25 ... +80 |
| <b>Derating temperature</b>                                                                                           | °C         | 40                |
| <b>Protection class IP</b>                                                                                            |            | IP00              |

#### Certificates/approvals:

## General Product Approval

## EMC



CCC



CSA



GOST



UL



C-TICK

## Test Certificates

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

## Shipping Approval



GL



LRS



PRS

## other

[Declaration of Conformity](#)

[Environmental Confirmations](#)

## UL/CSA ratings

### yielded mechanical performance (hp) / for three-phase squirrel cage motors

- at 220/230 V / at standard circuit
  - at 50 °C / rated value
- at 460/480 V / at standard circuit
  - at 50 °C / rated value
- at 200/208 V / at inside-delta circuit / at 50 °C / rated value
- at 220/230 V / at inside-delta circuit / at 50 °C / rated value
- at 460/480 V / at inside-delta circuit / at 50 °C / rated value

|    |     |
|----|-----|
| hp | 40  |
| hp | 75  |
| hp | 60  |
| hp | 75  |
| hp | 150 |

### Contact rating designation / for auxiliary contacts / according to UL

B300 / R300

## Further information:

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

### Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

### CAX-Online-Generator




<http://www.siemens.com/cax>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RW4435-2BC34/all>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3RW4435-2BC34](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RW4435-2BC34)



last change:

Feb 7, 2013