



SIRIUS soft starter 200-480 V 38 A, 110-250 V AC Screw terminals Analog output

|                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>product brand name</b>                               | SIRIUS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>product category</b>                                 | Hybrid switching devices                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>product designation</b>                              | Soft starter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>product type designation</b>                         | 3RW52                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>manufacturer's article number</b>                    | <ul style="list-style-type: none"> <li>• of standard HMI module usable</li> <li>• of high feature HMI module usable</li> <li>• of communication module PROFINET standard usable</li> <li>• of communication module PROFIBUS usable</li> <li>• of communication module Modbus TCP usable</li> <li>• of communication module Modbus RTU usable</li> <li>• of communication module Ethernet/IP</li> <li>• of circuit breaker usable at 400 V</li> <li>• of circuit breaker usable at 500 V</li> <li>• of circuit breaker usable at 400 V at inside-delta circuit</li> <li>• of circuit breaker usable at 500 V at inside-delta circuit</li> <li>• of the gG fuse usable up to 690 V</li> <li>• of the gG fuse usable at inside-delta circuit up to 500 V</li> <li>• of full range R fuse link for semiconductor protection usable up to 690 V</li> <li>• of back-up R fuse link for semiconductor protection usable up to 690 V</li> </ul> |
| <b>General technical data</b>                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>starting voltage [%]</b>                             | 30 ... 100 %                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>stopping voltage [%]</b>                             | 50 ... 50 %                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>start-up ramp time of soft starter</b>               | 0 ... 20 s                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>current limiting value [%] adjustable</b>            | 130 ... 700 %                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>certificate of suitability</b>                       | <ul style="list-style-type: none"> <li>• CE marking</li> <li>• UL approval</li> <li>• CSA approval</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>product component</b>                                | <ul style="list-style-type: none"> <li>• HMI-High Feature</li> <li>• is supported HMI-Standard</li> <li>• is supported HMI-High Feature</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>product feature integrated bypass contact system</b> | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>number of controlled phases</b>                      | 3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

[3RW5980-0HS00](#)

[3RW5980-0HF00](#)

[3RW5980-0CS00](#)

[3RW5980-0CP00](#)

[3RW5980-0CT00](#)

[3RW5980-0CR00](#)

[3RW5980-0CE00](#)

[3RV2032-4WA10: Type of coordination 1, Iq = 65 kA, CLASS 10](#)

[3RV2032-4WA10: Type of coordination 1, Iq = 10 kA, CLASS 10](#)

[3RV2032-4RA10: Type of coordination 1, Iq = 65 kA, CLASS 10](#)

[3RV2032-4RA10: Type of coordination 1, Iq = 10 kA, CLASS 10](#)

[3NA3824-6: Type of coordination 1, Iq = 65 kA](#)

[3NA3824-6: Type of coordination 1, Iq = 65 kA](#)

[3NE1820-0: Type of coordination 2, Iq = 65 kA](#)

[3NE8024-1: Type of coordination 2, Iq = 65 kA](#)

|                                                                                     |                                                                                 |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
| <b>trip class</b>                                                                   | CLASS 10A (default) / 10E / 20E; acc. to IEC 60947-4-2                          |
| <b>buffering time in the event of power failure</b>                                 |                                                                                 |
| • for main current circuit                                                          | 100 ms                                                                          |
| • for control circuit                                                               | 100 ms                                                                          |
| insulation voltage rated value                                                      | 600 V                                                                           |
| <b>degree of pollution</b>                                                          | 3, acc. to IEC 60947-4-2                                                        |
| <b>impulse voltage rated value</b>                                                  | 6 kV                                                                            |
| <b>blocking voltage of the thyristor maximum</b>                                    | 1 600 V                                                                         |
| <b>service factor</b>                                                               | 1                                                                               |
| <b>surge voltage resistance rated value</b>                                         | 6 kV                                                                            |
| <b>maximum permissible voltage for safe isolation</b>                               |                                                                                 |
| • between main and auxiliary circuit                                                | 600 V                                                                           |
| <b>shock resistance</b>                                                             | 15 g / 11 ms, from 12 g / 11 ms with potential contact lifting                  |
| <b>vibration resistance</b>                                                         | 15 mm to 6 Hz; 2g to 500 Hz                                                     |
| utilization category acc. to IEC 60947-4-2                                          | AC 53a                                                                          |
| <b>reference code acc. to IEC 81346-2</b>                                           | Q                                                                               |
| <b>Substance Prohibitance (Date)</b>                                                | 15.02.2018                                                                      |
| <b>product function</b>                                                             |                                                                                 |
| • ramp-up (soft starting)                                                           | Yes                                                                             |
| • ramp-down (soft stop)                                                             | Yes                                                                             |
| • Soft Torque                                                                       | Yes                                                                             |
| • adjustable current limitation                                                     | Yes                                                                             |
| • pump ramp down                                                                    | Yes                                                                             |
| • intrinsic device protection                                                       | Yes                                                                             |
| • motor overload protection                                                         | Yes; Electronic motor overload protection                                       |
| • evaluation of thermistor motor protection                                         | No                                                                              |
| • inside-delta circuit                                                              | Yes                                                                             |
| • auto-RESET                                                                        | Yes                                                                             |
| • manual RESET                                                                      | Yes                                                                             |
| • remote reset                                                                      | Yes; By turning off the control supply voltage                                  |
| • communication function                                                            | Yes                                                                             |
| • operating measured value display                                                  | Yes; Only in conjunction with special accessories                               |
| • error logbook                                                                     | Yes; Only in conjunction with special accessories                               |
| • via software parameterizable                                                      | No                                                                              |
| • via software configurable                                                         | Yes                                                                             |
| • <b>PROFInergy</b>                                                                 | Yes; in connection with the PROFINET Standard communication module              |
| • <b>firmware update</b>                                                            | Yes                                                                             |
| • <b>removable terminal for control circuit</b>                                     | Yes                                                                             |
| • torque control                                                                    | No                                                                              |
| • analog output                                                                     | Yes; 4 ... 20 mA (default) / 0 ... 10 V (parameterizable with High Feature HMI) |
| <b>Power Electronics</b>                                                            |                                                                                 |
| <b>operational current</b>                                                          |                                                                                 |
| • at 40 °C rated value                                                              | 38 A                                                                            |
| • at 50 °C rated value                                                              | 34 A                                                                            |
| • at 60 °C rated value                                                              | 31 A                                                                            |
| <b>operational current at inside-delta circuit</b>                                  |                                                                                 |
| • at 40 °C rated value                                                              | 65.8 A                                                                          |
| • at 50 °C rated value                                                              | 58 A                                                                            |
| • at 60 °C rated value                                                              | 52.8 A                                                                          |
| <b>operating voltage</b>                                                            |                                                                                 |
| • rated value                                                                       | 200 ... 480 V                                                                   |
| • at inside-delta circuit rated value                                               | 200 ... 480 V                                                                   |
| <b>relative negative tolerance of the operating voltage</b>                         | -15 %                                                                           |
| <b>relative positive tolerance of the operating voltage</b>                         | 10 %                                                                            |
| <b>relative negative tolerance of the operating voltage at inside-delta circuit</b> | -15 %                                                                           |
| <b>relative positive tolerance of the operating voltage at inside-delta circuit</b> | 10 %                                                                            |
| <b>operating power for 3-phase motors</b>                                           |                                                                                 |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                                                  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at 230 V at 40 °C rated value</li> <li>• at 230 V at inside-delta circuit at 40 °C rated value</li> <li>• at 400 V at 40 °C rated value</li> <li>• at 400 V at inside-delta circuit at 40 °C rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 11 kW<br>18.5 kW<br>18.5 kW<br>30 kW                                                                                                                             |
| <b>Operating frequency 1 rated value</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 50 Hz                                                                                                                                                            |
| <b>Operating frequency 2 rated value</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 60 Hz                                                                                                                                                            |
| <b>relative negative tolerance of the operating frequency</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | -10 %                                                                                                                                                            |
| <b>relative positive tolerance of the operating frequency</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 10 %                                                                                                                                                             |
| <b>adjustable motor current</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at rotary coding switch on switch position 1</li> <li>• at rotary coding switch on switch position 2</li> <li>• at rotary coding switch on switch position 3</li> <li>• at rotary coding switch on switch position 4</li> <li>• at rotary coding switch on switch position 5</li> <li>• at rotary coding switch on switch position 6</li> <li>• at rotary coding switch on switch position 7</li> <li>• at rotary coding switch on switch position 8</li> <li>• at rotary coding switch on switch position 9</li> <li>• at rotary coding switch on switch position 10</li> <li>• at rotary coding switch on switch position 11</li> <li>• at rotary coding switch on switch position 12</li> <li>• at rotary coding switch on switch position 13</li> <li>• at rotary coding switch on switch position 14</li> <li>• at rotary coding switch on switch position 15</li> <li>• at rotary coding switch on switch position 16</li> <li>• minimum</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                         | 15.5 A<br>17 A<br>18.5 A<br>20 A<br>21.5 A<br>23 A<br>24.5 A<br>26 A<br>27.5 A<br>29 A<br>30.5 A<br>32 A<br>33.5 A<br>35 A<br>36.5 A<br>38 A<br>15.5 A           |
| <b>adjustable motor current</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• for inside-delta circuit at rotary coding switch on switch position 1</li> <li>• for inside-delta circuit at rotary coding switch on switch position 2</li> <li>• for inside-delta circuit at rotary coding switch on switch position 3</li> <li>• for inside-delta circuit at rotary coding switch on switch position 4</li> <li>• for inside-delta circuit at rotary coding switch on switch position 5</li> <li>• for inside-delta circuit at rotary coding switch on switch position 6</li> <li>• for inside-delta circuit at rotary coding switch on switch position 7</li> <li>• for inside-delta circuit at rotary coding switch on switch position 8</li> <li>• for inside-delta circuit at rotary coding switch on switch position 9</li> <li>• for inside-delta circuit at rotary coding switch on switch position 10</li> <li>• for inside-delta circuit at rotary coding switch on switch position 11</li> <li>• for inside-delta circuit at rotary coding switch on switch position 12</li> <li>• for inside-delta circuit at rotary coding switch on switch position 13</li> <li>• for inside-delta circuit at rotary coding switch on switch position 14</li> <li>• for inside-delta circuit at rotary coding switch on switch position 15</li> <li>• for inside-delta circuit at rotary coding switch on switch position 16</li> <li>• at inside-delta circuit minimum</li> </ul> | 26.8 A<br>29.4 A<br>32 A<br>34.6 A<br>37.2 A<br>39.8 A<br>42.4 A<br>45 A<br>47.6 A<br>50.2 A<br>52.8 A<br>55.4 A<br>58 A<br>60.6 A<br>63.2 A<br>65.8 A<br>26.8 A |
| <b>minimum load [%]</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 15 %; Relative to smallest settable I <sub>e</sub>                                                                                                               |
| <b>power loss [W] for rated value of the current at AC</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 40 °C after startup</li> <li>• at 50 °C after startup</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 23 W<br>22 W                                                                                                                                                     |

|                                                                                   |                                                                                                                                                                                |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at 60 °C after startup</li> </ul>        | 21 W                                                                                                                                                                           |
| <b>power loss [W] at AC at current limitation 350 %</b>                           |                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• at 40 °C during startup</li> </ul>       | 628 W                                                                                                                                                                          |
| <ul style="list-style-type: none"> <li>• at 50 °C during startup</li> </ul>       | 526 W                                                                                                                                                                          |
| <ul style="list-style-type: none"> <li>• at 60 °C during startup</li> </ul>       | 464 W                                                                                                                                                                          |
| <b>Control circuit/ Control</b>                                                   |                                                                                                                                                                                |
| <b>type of voltage of the control supply voltage</b>                              | AC                                                                                                                                                                             |
| <b>control supply voltage at AC</b>                                               |                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                      | 110 ... 250 V                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 60 Hz</li> </ul>                      | 110 ... 250 V                                                                                                                                                                  |
| <b>relative negative tolerance of the control supply voltage at AC at 50 Hz</b>   | -15 %                                                                                                                                                                          |
| <b>relative positive tolerance of the control supply voltage at AC at 50 Hz</b>   | 10 %                                                                                                                                                                           |
| <b>relative negative tolerance of the control supply voltage at AC at 60 Hz</b>   | -15 %                                                                                                                                                                          |
| <b>relative positive tolerance of the control supply voltage at AC at 60 Hz</b>   | 10 %                                                                                                                                                                           |
| <b>control supply voltage frequency</b>                                           | 50 ... 60 Hz                                                                                                                                                                   |
| <b>relative negative tolerance of the control supply voltage frequency</b>        | -10 %                                                                                                                                                                          |
| <b>relative positive tolerance of the control supply voltage frequency</b>        | 10 %                                                                                                                                                                           |
| <b>control supply current in standby mode rated value</b>                         | 30 mA                                                                                                                                                                          |
| <b>holding current in bypass operation rated value</b>                            | 75 mA                                                                                                                                                                          |
| <b>locked-rotor current at close of bypass contact maximum</b>                    | 0.17 A                                                                                                                                                                         |
| <b>inrush current peak at application of control supply voltage maximum</b>       | 12.2 A                                                                                                                                                                         |
| <b>duration of inrush current peak at application of control supply voltage</b>   | 2.2 ms                                                                                                                                                                         |
| <b>design of the overvoltage protection</b>                                       | Varistor                                                                                                                                                                       |
| <b>design of short-circuit protection for control circuit</b>                     | 4 A gG fuse (Icu=1 kA), 6 A quick-acting fuse (Icu=1 kA), C1 miniature circuit breaker (Icu= 600 A), C6 miniature circuit breaker (Icu= 300 A); Is not part of scope of supply |
| <b>Inputs/ Outputs</b>                                                            |                                                                                                                                                                                |
| <b>number of digital inputs</b>                                                   | 1                                                                                                                                                                              |
| <b>number of digital outputs</b>                                                  | 3                                                                                                                                                                              |
| <ul style="list-style-type: none"> <li>• not parameterizable</li> </ul>           | 2                                                                                                                                                                              |
| <b>digital output version</b>                                                     | 2 normally-open contacts (NO) / 1 changeover contact (CO)                                                                                                                      |
| <b>number of analog outputs</b>                                                   | 1                                                                                                                                                                              |
| <b>switching capacity current of the relay outputs</b>                            |                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• at AC-15 at 250 V rated value</li> </ul> | 3 A                                                                                                                                                                            |
| <ul style="list-style-type: none"> <li>• at DC-13 at 24 V rated value</li> </ul>  | 1 A                                                                                                                                                                            |
| <b>Installation/ mounting/ dimensions</b>                                         |                                                                                                                                                                                |
| <b>mounting position</b>                                                          | with vertical mounting surface +/-90° rotatable, with vertical mounting surface +/- 22.5° tiltable to the front and back                                                       |
| <b>fastening method</b>                                                           | screw fixing                                                                                                                                                                   |
| <b>height</b>                                                                     | 275 mm                                                                                                                                                                         |
| <b>width</b>                                                                      | 170 mm                                                                                                                                                                         |
| <b>depth</b>                                                                      | 152 mm                                                                                                                                                                         |
| <b>required spacing with side-by-side mounting</b>                                |                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• forwards</li> </ul>                      | 10 mm                                                                                                                                                                          |
| <ul style="list-style-type: none"> <li>• backwards</li> </ul>                     | 0 mm                                                                                                                                                                           |
| <ul style="list-style-type: none"> <li>• upwards</li> </ul>                       | 100 mm                                                                                                                                                                         |
| <ul style="list-style-type: none"> <li>• downwards</li> </ul>                     | 75 mm                                                                                                                                                                          |
| <ul style="list-style-type: none"> <li>• at the side</li> </ul>                   | 5 mm                                                                                                                                                                           |
| <b>weight without packaging</b>                                                   | 2.3 kg                                                                                                                                                                         |
| <b>Connections/ Terminals</b>                                                     |                                                                                                                                                                                |
| <b>type of electrical connection</b>                                              |                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• for main current circuit</li> </ul>      | screw-type terminals                                                                                                                                                           |
| <ul style="list-style-type: none"> <li>• for control circuit</li> </ul>           | screw-type terminals                                                                                                                                                           |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>• for main contacts <ul style="list-style-type: none"> <li>— solid</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>• at AWG cables for main current circuit solid</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 2x (1.0 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 10 mm <sup>2</sup> )<br>2x (1.0 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6.0 mm <sup>2</sup> )<br>2x (16 ... 12), 2x (14 ... 8)                                                                                                                                                                                                                                                                                                                                                                       |
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>• for control circuit solid</li> <li>• for control circuit finely stranded with core end processing</li> <li>• at AWG cables for control circuit solid</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 1x (0.5 ... 4.0 mm <sup>2</sup> ), 2x (0.5 ... 2.5 mm <sup>2</sup> )<br>1x (0.5 ... 2.5 mm <sup>2</sup> ), 2x (0.5 ... 1.5 mm <sup>2</sup> )<br>1x (20 ... 12), 2x (20 ... 14)                                                                                                                                                                                                                                                                                                                                                                     |
| <b>wire length</b> <ul style="list-style-type: none"> <li>• between soft starter and motor maximum</li> <li>• at the digital inputs at AC maximum</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 800 m<br>100 m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>tightening torque</b> <ul style="list-style-type: none"> <li>• for main contacts with screw-type terminals</li> <li>• for auxiliary and control contacts with screw-type terminals</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 2 ... 2.5 N·m<br>0.8 ... 1.2 N·m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>tightening torque [lbf·in]</b> <ul style="list-style-type: none"> <li>• for main contacts with screw-type terminals</li> <li>• for auxiliary and control contacts with screw-type terminals</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 18 ... 22 lbf·in<br>7 ... 10.3 lbf·in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Ambient conditions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| installation altitude at height above sea level maximum                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 5 000 m; Derating as of 1000 m, see catalog                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>ambient temperature</b> <ul style="list-style-type: none"> <li>• during operation</li> <li>• during storage and transport</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | -25 ... +60 °C; Please observe derating at temperatures of 40 °C or above<br>-40 ... +80 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>environmental category</b> <ul style="list-style-type: none"> <li>• during operation acc. to IEC 60721</li> <li>• during storage acc. to IEC 60721</li> <li>• during transport acc. to IEC 60721</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 3K6 (no ice formation, only occasional condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6<br>1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4<br>2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m)                                                                                                                                                                                                                                                                  |
| <b>EMC emitted interference</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | acc. to IEC 60947-4-2: Class A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Communication/ Protocol</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>communication module is supported</b> <ul style="list-style-type: none"> <li>• PROFINET standard</li> <li>• EtherNet/IP</li> <li>• Modbus RTU</li> <li>• Modbus TCP</li> <li>• PROFIBUS</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Yes<br>Yes<br>Yes<br>Yes<br>Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>UL/CSA ratings</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>manufacturer's article number</b> <ul style="list-style-type: none"> <li>• of circuit breaker <ul style="list-style-type: none"> <li>— usable for Standard Faults at 460/480 V according to UL</li> <li>— usable for High Faults at 460/480 V according to UL</li> <li>— usable for Standard Faults at 460/480 V at inside-delta circuit according to UL</li> <li>— usable for High Faults at 460/480 V at inside-delta circuit according to UL</li> <li>— usable for Standard Faults at 575/600 V according to UL</li> <li>— usable for Standard Faults at 575/600 V at inside-delta circuit according to UL</li> </ul> </li> <li>• of the fuse <ul style="list-style-type: none"> <li>— usable for Standard Faults up to 575/600 V according to UL</li> <li>— usable for High Faults up to 575/600 V according to UL</li> <li>— usable for Standard Faults at inside-delta circuit up to 575/600 V according to UL</li> </ul> </li> </ul> | Siemens type: 3RV2742, max. 70 A or 3VA51, max. 125 A; Iq = 5 kA<br>Siemens type: 3RV2742, max. 40 A or 3VA51, max. 60 A; Iq max = 65 kA<br>Siemens type: 3RV2742, max. 70 A or 3VA51, max. 125 A; Iq = 5 kA<br>Siemens type: 3VA51, max. 60 A; Iq max = 65 kA<br>Siemens type: 3RV2742, max. 70 A or 3VA51, max. 125 A; Iq = 5 kA<br>Siemens type: 3RV2742, max. 70 A or 3VA51, max. 125 A; Iq = 5 kA<br>Type: Class RK5 / K5, max. 150 A; Iq = 5 kA<br>Type: Class J / L, max. 150 A; Iq = 100 kA<br>Type: Class RK5 / K5, max. 150 A; Iq = 5 kA |

|                                                                                  |                                                        |
|----------------------------------------------------------------------------------|--------------------------------------------------------|
| — usable for High Faults at inside-delta circuit up to 575/600 V according to UL | Type: Class J / L, max. 150 A; I <sub>q</sub> = 100 kA |
| <b>operating power [hp] for 3-phase motors</b>                                   |                                                        |
| • at 200/208 V at 50 °C rated value                                              | 10 hp                                                  |
| • at 220/230 V at 50 °C rated value                                              | 10 hp                                                  |
| • at 460/480 V at 50 °C rated value                                              | 20 hp                                                  |
| • at 200/208 V at inside-delta circuit at 50 °C rated value                      | 15 hp                                                  |
| • at 220/230 V at inside-delta circuit at 50 °C rated value                      | 20 hp                                                  |
| • at 460/480 V at inside-delta circuit at 50 °C rated value                      | 40 hp                                                  |
| <b>contact rating of auxiliary contacts according to UL</b>                      | R300-B300                                              |

|                                                           |                                                  |
|-----------------------------------------------------------|--------------------------------------------------|
| <b>Safety related data</b>                                |                                                  |
| <b>protection class IP on the front acc. to IEC 60529</b> | IP20                                             |
| <b>touch protection on the front acc. to IEC 60529</b>    | finger-safe, for vertical contact from the front |
| <b>electromagnetic compatibility</b>                      | in accordance with IEC 60947-4-2                 |

|                                |     |                           |
|--------------------------------|-----|---------------------------|
| <b>Certificates/ approvals</b> |     |                           |
| General Product Approval       | EMC | Declaration of Conformity |



|                           |                   |                   |
|---------------------------|-------------------|-------------------|
| Declaration of Conformity | Test Certificates | Marine / Shipping |
|---------------------------|-------------------|-------------------|

[UK Declaration of Conformity](#)

[Type Test Certificates/Test Report](#)



|                   |       |
|-------------------|-------|
| Marine / Shipping | other |
|-------------------|-------|



[Confirmation](#)

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5217-1AC14>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5217-1AC14>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5217-1AC14>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5217-1AC14&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5217-1AC14&lang=en)

Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current




<https://support.industry.siemens.com/cs/ww/en/ps/3RW5217-1AC14/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5217-1AC14&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>





last modified:

9/21/2021 