



Bypass kit for 3RW50 Size S12, 370 A to 570 A

product designation	Bypass unit		
design of the product	370 ... 570 A		
manufacturer's article number of soft starter	3RW5075, 3RW5076, 3RW5077		
•			
Substance Prohibittance (Date)	09/23/2019		
Ambient conditions			
ambient temperature during storage	-40 ... +80 °C		
Approvals Certificates			
General Product Approval		EMV	For use in hazardous locations



[Confirmation](#)



EG-Konf.



[KC](#)

[Miscellaneous](#)

Test Certificates	Marine / Shipping	other
Type Test Certificates/Test Report	   	Confirmation

Environment

[Environmental Confirmations](#)

Further information

Information on the packaging

<http://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5907-0BY00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5907-0BY00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5907-0BY00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5907-0BY00&lang=en

Characteristic: Tripping characteristics, I²t, Let-through current
<https://support.industry.siemens.com/cs/ww/en/ps/3RW5907-0BY00/char>

Characteristic: Installation altitude
<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5907-0BY00&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)
<https://support.industry.siemens.com/cs/ww/en/view/101494917>

last modified:

1/12/2021 

