



Spring flap for 3RW55/52 without cutout

|                                |                |
|--------------------------------|----------------|
| product designation            | Hinged cover   |
| design of the product          | Without cutout |
| manufacturer's article number  |                |
| • of soft starter              | 3RW51          |
| • of soft starter              | 3RW52          |
| • of soft starter              | 3RW55          |
| Substance Prohibittance (Date) | 15.02.2018     |

|                                    |                |
|------------------------------------|----------------|
| Ambient conditions                 |                |
| ambient temperature during storage | -40 ... +80 °C |

|                          |                           |                   |                   |
|--------------------------|---------------------------|-------------------|-------------------|
| Certificates/ approvals  |                           |                   |                   |
| General Product Approval | Declaration of Conformity | Test Certificates | Marine / Shipping |



[UK Declaration of Conformity](#)



[Type Test Certificates/Test Report](#)



|                   |       |
|-------------------|-------|
| Marine / Shipping | other |
|-------------------|-------|



[Confirmation](#)

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5950-0GL20>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5950-0GL20>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5950-0GL20>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5950-0GL20&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5950-0GL20&lang=en)

Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5950-0GL20/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5950-0GL20&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

last modified:

1/18/2021 

