

AS-I CABLE TRAPEZOIDAL YELLOW, TPE,
OIL-RESISTANT, 2 X 1,5QMM,
1000M 1 PIECE = 1000M



General technical data:

Design of the product		AS-Interface shaped cables
Colour		yellow (AS-Interface)
Material		TPE
Quantity		1 km drum

Mechanical data:

Without silicone precipitation		yes
bending radius / according to DIN VDE 0298 Part 300		
• fixed / min	m	12
• freely movable / min	m	24
Without halogens		no
Flexibility		good
Bending behavior according / according to DIN VDE 0472 Part 603		no break after 30000 reverse bending cycles
Core colours		brown, blue

Ambient conditions:

Fire behavior		flame-retardant according to IEC 60332-1;VDE 0482 T. 265-2-1;UL 1581 sec. 1061 cable flame;UL 1581 sec. 1060 CSA FT1
resistance to oil		resistant

Ozone / and weather resistant		resistant
Temperature range		
• stationary	°C	-40 ... +105
• moved	°C	-30 ... +105

Certificates/ approvals:

Approvals / Canada	CSA		C22.2 No.210.2 AWM
Approvals / USA	UL		UL 758 AWM
Monitored expertise (VDE)			no
General Product Approval	Shipping Approval	other	



[Declaration of Conformity](#)

[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RX9014-0AA00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RX9014-0AA00

last change:

Jul 1, 2013