

ILLUMINATED PUSHBUTTON, 16MM, ROUND,
PLASTIC, GREEN, BUTTON, FLAT

Actuator/ signaling device:		
Design of the product		Single device round
Design of the operating mechanism		Illuminated pushbutton
Functionality / of the actuator		Momentary contact type
Type of unlocking device		without
Color / of the activation element		Green
Material / of the activation element		plastic
Shape / of the activation element		Flat pushbutton
Number of switching positions		2
Product component / front ring		Yes
Material / of the front ring		plastic
Color / of the front ring		black
Design of the front ring		Standard
Product function / EMERGENCY STOP function		No
Holder:		
Material / of the holder		Plastic
General technical details:		
Resistance against shock / for devices with incandescent lamp / according to IEC 60068-2-27		<= 30g
Resistance against vibration / according to IEC 60068-2-6		20 ... 200 Hz: 5g
Operating cycles / maximum	1/h	1,000
Mechanical operating cycles as operating time / typical		3,000,000
Reference code		
• according to DIN EN 61346-2		S
• according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		S
Tightening torque / of the screws in the bracket / maximum	N·m	0.4
Ambient temperature		
• during operating	°C	-25 ... +70
• during storage	°C	-40 ... +80
Protection class IP		IP65

climatic class / during the operating phase / according to EN 60721		3K6
Mounting type		front mounting
Shape / of the installation hole		round
Installation width	mm	19
Mounting diameter	mm	16
Mounting height	mm	8
Mounting depth	mm	50

Certificates/ approvals:

General Product Approval



[Special Test Certificate](#)

other

[Confirmation](#)

[other](#)

[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator


<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SB2001-0AE01/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SB2001-0AE01



Length **a** of spacing bolts:
a = $44_{-0,2}$ minus front plate thickness.

When using name plates, the
length **a** is reduced by 0.8 mm.

last change:

Jul 7, 2014