
SIEMENS

Product data sheet 3SB2455-0F



SWITCHING ELEMENT, 1NC, 1NC, SOLDER PIN CONNECTION

| Contact block/ lampholder: | | | |
|--------------------------------------------------------|-----------------------|--|--|
| Product designation | contact block | | |
| Number of NC contacts / for auxiliary contacts | 2 | | |
| Number of NO contacts / for auxiliary contacts | 0 | | |
| Number of changeover contacts / for auxiliary contacts | 0 | | |
| Product function / positive opening | Yes | | |
| Number of lampholders | 0 | | |
| Design of the electrical connection | solder pin connectors | | |

| General technical data: | | | |
|-------------------------------------|---|-------|--|
| Voltage type / of operating voltage | | AC/DC | |
| Operating voltage | | | |
| • at 50 Hz / at AC | | | |
| • rated value | V | 5 230 | |
| • at 60 Hz / at AC | | | |
| • rated value | V | 5 230 | |
| • for DC | | | |
| • rated value | V | 5 230 | |
| Operating current | | | |
| • at AC-12 | | | |
| • at 24 V / rated value | Α | 10 | |

| • at 60 V / rated value | Α | 10 |
|------------------------------------------------------------------------------------------------|----|---------------|
| • at 110 V / rated value | Α | 10 |
| • at 230 V / rated value | Α | 10 |
| • at AC-15 | | |
| • at 24 V / rated value | Α | 4 |
| • at 60 V / rated value | Α | 4 |
| • at 110 V / rated value | Α | 4 |
| • at 230 V / rated value | Α | 4 |
| • at DC-12 | | |
| • at 24 V / rated value | Α | 6 |
| • at 60 V / rated value | Α | 5 |
| • at 110 V / rated value | Α | 2.5 |
| • at 230 V / rated value | Α | 1 |
| • at DC-13 | | |
| • at 24 V / rated value | Α | 3 |
| • at 60 V / rated value | Α | 1.2 |
| • at 110 V / rated value | Α | 0.7 |
| • at 230 V / rated value | Α | 0.3 |
| Resistance against shock / for devices without incandescent lamp / according to IEC 60068-2-27 | | <= 50g |
| Resistance against vibration / according to IEC 60068-2-6 | | 20 200 Hz: 5g |
| Reference code / according to DIN EN 61346-2 | | S |
| Reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750 | | S |
| Ambient temperature | | |
| during operating | °C | -25 +70 |
| during storage | °C | -40 +80 |
| Protection class IP / of the terminal | | IP20 |
| protection type IP / of the enclosure | | IP40 |
| Mounting type | | clip-on |
| Width | mm | 18 |
| Height | mm | 19 |
| Depth | mm | 29 |
| | | |

Certificates/ approvals:

General Product Approval



Declaration of Conformity











other

Confirmation

Environmental Confirmations

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrial-controls/mall

Cax online generator

http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

 $\underline{\text{http://support.automation.siemens.com/WW/view/en/3SB2455-0F/all}}$

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

 $\underline{\text{http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SB2455-0F}$

last change: Jun 16, 2014