

22MM PLASTIC ROUND ACTUATOR: OMR KEY-OPER.SWITCH  
W. 2 KEYS 2 SWITCH POSITIONS O-I LATCHING LOCK NO  
73034, REMOVAL POS. O Z=WITHOUT HOLDER BLACK

|                                             |                     |
|---------------------------------------------|---------------------|
| Design of the product                       | Single device round |
| Enclosure:                                  |                     |
| Number of command points                    | 1                   |
| Actuator:                                   |                     |
| Design of the operating mechanism           | Key-operated switch |
| Manner of function of the actuating element | Latching            |
| Product extension optional Light source     | No                  |
| Color                                       |                     |
| • of the actuating element                  | black               |
| Material of the actuating element           | plastic             |
| Outer diameter of the actuating element     | 28.5 mm             |
| Type of unlocking device                    | key unlatching      |
| Number of switching positions               | 2                   |
| Switch position for key distraction         | O                   |
| Actuating angle                             |                     |
| • clockwise                                 | 50°                 |
| Lock make                                   | O.M.R.              |
| Front ring:                                 |                     |
| Product component front ring                | Yes                 |
| Design of the front ring                    | Standard            |
| Material of the front ring                  | plastic             |
| Color of the front ring                     | black               |
| General technical data:                     |                     |
| Product function                            |                     |
| • EMERGENCY OFF function                    | No                  |
| • EMERGENCY STOP function                   | No                  |
| Protection class IP                         | IP66                |
| Vibration resistance                        |                     |
| • acc. to IEC 60068-2-6                     | 20 ... 200 Hz: 5g   |
| Operating frequency maximum                 | 1 000 1/h           |
| Mechanical service life (switching cycles)  |                     |
| • typical                                   | 300 000             |
| Equipment marking                           |                     |

- acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750
- acc. to DIN EN 61346-2
- acc. to DIN EN 81346-2

S  
S  
S

#### Ambient conditions:

##### Ambient temperature

- during operation
- during storage

-25 ... +70 °C

-40 ... +80 °C

Environmental category during operation acc. to IEC 60721

3K6

#### Installation/ mounting/ dimensions:

##### Mounting type

front mounting

##### Shape of the installation opening

round

##### Mounting diameter

22 mm

##### Mounting height

64 mm

##### Installation width

28.5 mm

##### Installation depth

29 mm

#### Certificates/approvals

##### General Product Approval

##### Declaration of Conformity

##### Test Certificates

##### Shipping Approval



spezielle  
Prüfbescheinigungen  
n



##### Shipping Approval

##### other



Bestätigungen

sonstig

##### other

Umweltbestätigung

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB3000-3AJ01-Z B01>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB3000-3AJ01-Z B01>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3SB3000-3AJ01-Z B01>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SB3000-3AJ01-Z B01&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB3000-3AJ01-Z B01&lang=en)

**last modified:**

08/18/2016