

26X26MM PLASTIC SQUARE ACTUATOR: SELECTOR SWITCH
LEFT MOMEN.,RI.LATCH.CONT.TYPE 3 SWITCH POSITIONS I-O-
II NON-ILLUMINATED Z=WITHOUT HOLDER BLACK

Design of the product

Single device square

Enclosure:

Number of command points

1

Actuator:

Design of the operating mechanism

selector switch

Manner of function of the actuating element

Momentary contact (left), latching (right)

Product extension optional Light source

No

Color

- of the actuating element

black

Material of the actuating element

plastic

Type of unlocking device

rotate-to-unlatch mechanism

Number of switching positions

3

Actuating angle

- clockwise
- anticlockwise

50°

50°

Front ring:

Product component front ring

Yes

Design of the front ring

Standard

Material of the front ring

plastic

Color of the front ring

black

General technical data:

Product function

- EMERGENCY OFF function
- EMERGENCY STOP function

No

No

Protection class IP

IP66

Vibration resistance

- acc. to IEC 60068-2-6

20 ... 200 Hz: 5g

Operating frequency maximum

1 000 1/h

Mechanical service life (switching cycles)

- typical

300 000

Equipment marking

- acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750
- acc. to DIN EN 61346-2

S

S

- acc. to DIN EN 81346-2

S

Ambient conditions:

Ambient temperature

- during operation
- during storage

-25 ... +70 °C

-40 ... +80 °C

Environmental category during operation acc. to IEC 60721

3K6

Installation/ mounting/ dimensions:

Mounting type

front mounting

Shape of the installation opening

square

Mounting height

24 mm

Installation width

30 mm

Installation depth

29 mm

Certificates/approvals

General Product Approval

Declaration of Conformity

Test Certificates

Shipping Approval



EG-Konf.

[spezielle
Prüfbescheinigungen](#)
[n](#)



ABS

Shipping Approval

other



DNV



LRS



PRS



RINA

[sonstig](#)

[Bestätigungen](#)

other

[Umweltbestätigung](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB3110-2GA11-Z B01>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB3110-2GA11-Z B01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB3110-2GA11-Z B01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB3110-2GA11-Z B01&lang=en

last modified:

08/18/2016