



22MM PLASTIC ROUND COMPLETE UNIT
COMBINATION: ILLUMINATED PUSHBUTTON
MOMENTARY CONTACT TYPE WITH FLAT BUTTON
ILLUMINATED WITH INTEGRATED LED 230V AC SPRING-
LOADED TERMINAL,
1NO WITH HOLDER YELLOW

Actuator / signaling device:

Design of the product	Complete unit, round
Design of the operating mechanism	Illuminated pushbutton
Type of unlocking device	without
Color / of the activation element	Yellow
Material / of the activation element	plastic
Shape / of the activation element	Flat pushbutton
Number of switching positions	2
Product component / front ring	Yes
Material / of the front ring	plastic
Color / of the front ring	black
Design of the front ring	Standard
Product function / EMERGENCY STOP function	No

Holder:

Material / of the holder	Plastic
--------------------------	---------

Contact block / lampholder

Design of the electrical connection	spring-loaded terminals
Number of switching elements	1
Number of NC contacts / for auxiliary contacts	0

Number of NO contacts / for auxiliary contacts		1
Number of change-over switches / for auxiliary contacts		0
Product function / positive opening		No
Number of lampholders		1
Execution of the mounting		integrated LED
Product component / fluorescent materials		Yes
Product extension / optional / fluorescent materials		Yes

Accessories:

Product component / holder for 3 switching elements

Yes

General technical details:

Type of voltage / of the supply voltage / of the fluorescent material

AC

• of the fluorescent material / at 60 Hz / for AC / rated value

V

230

• of the fluorescent material / at 50 Hz / for AC / rated value

V

230

Type of voltage / of the operating voltage

AC

Operating voltage / rated value

• minimum

V

190

• maximum

V

265

Operating current

• at AC-12

• at 24 V / rated value

A

10

• at 48 V / rated value

A

10

• at 110 V / rated value

A

10

• at 230 V / rated value

A

10

• at 400 V / rated value

A

10

• at AC-15

• at 24 V / rated value

A

6

• at 48 V / rated value

A

6

• at 110 V / rated value

A

6

• at 230 V / rated value

A

6

• at 400 V / rated value

A

3

• at DC-12

• at 24 V / rated value

A

10

• at 48 V / rated value

A

5

• at 110 V / rated value

A

2.5

• at 230 V / rated value

A

1

• at DC-13

• at 24 V / rated value

A

3

• at 48 V / rated value

A

1.5

• at 110 V / rated value	A	0.7
• at 230 V / rated value	A	0.3
Resistance against shock		
• for devices without incandescent lamp / according to IEC 60068-2-27		<= 50g
Resistance against vibration / according to IEC 60068-2-6		20 ... 200 Hz: 5g
Operating cycles / maximum	1/h	1,000
Mechanical operating cycles as operating time / typical		3,000,000
Item designation		
• according to DIN EN 61346-2		S
• according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		S
Tightening torque / of the screws in the bracket / maximum	N·m	1
Ambient temperature		
• during operating	°C	-25 ... +70
• during storage	°C	-40 ... +80
Protection class IP		IP66
climatic class / during the operating phase / according to EN 60721		3K6
Type of mounting		front mounting
Shape / of the installation hole		round
Installation width	mm	28.5
Mounting diameter	mm	22
Mounting height	mm	8
Mounting depth	mm	49

Certificates/approvals:

General Product Approval



CSA



GOST



UL



EG-Konf.

Test Certificates

[Special Test Certificate](#)

Shipping Approval



ABS



DNV



LRS



PRS



RINA

other

[Confirmation](#)

[other](#)

[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SB3253-0AA31-0CC0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SB3253-0AA31-0CC0

last change:

Jan 21, 2013