

SIRIUS 3SB3 SET SUPPLY FOR FA. BMW ACCORD. TO  
OFFER 47047

### Actuator:

|                                            |  |                        |
|--------------------------------------------|--|------------------------|
| Functionality / of the actuator            |  | Momentary contact type |
| Type of unlocking device                   |  | without                |
| Color / of the activation element          |  | black                  |
| Material / of the activation element       |  | plastic                |
| Shape / of the activation element          |  | round                  |
| Number of switching positions              |  | 2                      |
| Product component / front ring             |  | No                     |
| Design of the front ring                   |  | Standard               |
| Product function / EMERGENCY STOP function |  | No                     |

### Holder:

|                          |  |         |
|--------------------------|--|---------|
| Material / of the holder |  | Plastic |
|--------------------------|--|---------|

### Contact block/ lampholder:

|                                                      |  |    |
|------------------------------------------------------|--|----|
| Product function / positive opening                  |  | No |
| Product component / fluorescent materials            |  | No |
| Product extension / optional / fluorescent materials |  | No |

### Accessories:

|                                                     |  |    |
|-----------------------------------------------------|--|----|
| Product component / holder for 3 switching elements |  | No |
|-----------------------------------------------------|--|----|

### General technical data:

|                                                                     |     |                   |
|---------------------------------------------------------------------|-----|-------------------|
| Resistance against vibration / according to IEC 60068-2-6           |     | 20 ... 200 Hz: 5g |
| Operating cycles / maximum                                          | 1/h | 1,000             |
| Mechanical operating cycles as operating time / typical             |     | 10,000,000        |
| Tightening torque / of the screws in the bracket / maximum          | N·m | 1                 |
| Ambient temperature                                                 |     |                   |
| • during storage                                                    | °C  | -40 ... +80       |
| climatic class / during the operating phase / according to EN 60721 |     | 3K6               |
| Shape / of the installation hole                                    |     | round             |
| Mounting diameter                                                   | mm  | 22                |
| Mounting height                                                     | mm  | 49                |
| Mounting depth                                                      | mm  | 49                |

## Certificates/ approvals:

### General Product Approval



CSA



EG-Konf.

### Test Certificates

[Special Test Certificate](#)

### Shipping Approval



ABS



DNV



LRS



PRS



RINA

### other

[Confirmation](#)

[other](#)

[Environmental Confirmations](#)

## Further information:

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

### Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

### Cax online generator

<http://www.siemens.com/cax>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SB3288-0AA11/all>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3SB3288-0AA11](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SB3288-0AA11)

last change:

Jul 7, 2014