
## **SIEMENS**

Product data sheet 3SB3304-6AA60



26X26MM PLASTIC SQUARE COMPLETE UNIT COMBINATION: INDICATOR LIGHT WITH SMOOTH LENSE NON-ILLUMINATED WITH LAMP HOLDER BA 9S WITHOUT LAMP SCREW TERMINAL WITH HOLDER WHITE

Actuator:	
Design of the product	Complete unit, square
Design of the operating mechanism	indicator light
Color / of the activation element	White
Material / of the activation element	plastic
Shape / of the activation element	Smooth lens
Number of switching positions	0
Product component / front ring	No
Product function / EMERGENCY STOP function	No

Holder:	
Material / of the holder	Plastic

Contact block/ lampholder:			
Design of the electrical connection		screw-type terminals	
Number of switching elements		0	
Number of NC contacts / for auxiliary contacts		0	
Number of NO contacts / for auxiliary contacts		0	
Number of changeover contacts / for auxiliary contacts		0	
Product function / positive opening		No	
Number of lampholders		1	

Execution of the mounting	BA 9s, without lamp
Product component / fluorescent materials	No
Product extension / optional / fluorescent materials	Yes

General technical data:				
Voltage type / of operating voltage		AC/DC		
Operating voltage / rated value				
• minimum	V	5		
• maximum	V	400		
Resistance against shock				
<ul> <li>for devices with incandescent lamp / according to IEC 60068-2- 27</li> </ul>		<= 30g		
• for devices without incandescent lamp / according to IEC 60068-2-27		<= 50g		
Resistance against vibration / according to IEC 60068-2-6		20 200 Hz: 5g		
Reference code				
<ul> <li>according to DIN EN 61346-2</li> </ul>		P		
<ul> <li>according to DIN 40719 extended according to IEC 204-2 / according to IEC 750</li> </ul>		Н		
Tightening torque / of the screws in the bracket / maximum	N⋅m	1		
Ambient temperature				
during operating	°C	-25 +60		
during storage	°C	-40 +80		
Protection class IP		IP66		
climatic class / during the operating phase / according to EN 60721		3K6		
Mounting type		front mounting		
Shape / of the installation hole		square		
Installation width	mm	30		
Mounting height	mm	7		
Mounting depth	mm	49		

### Certificates/ approvals:

### **General Product Approval**

# Declaration of Conformity

#### **Test Certificates**









Special Test Certificate

### **Shipping Approval**











other

Confirmation

other

Environmental Confirmations

### **Further information:**

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

 $\underline{\text{http://www.siemens.com/industrial-controls/mall}}$ 

Cax online generator

http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/3SB3304-6AA60/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

 $\underline{\text{http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=3SB3304-6AA60}}$ 

last change: Jul 7, 2014