

SELECTOR SWITCH, 22MM, ROUND, METAL, GREEN, SHORT KNOB, 3 SWITCH POSITIONS I-O-II, LATCHING, ACTUATING ANGLE 2X50 DEG., WITH HOLDER, Z=50X PACK



Figure similar

|                                             |                             |
|---------------------------------------------|-----------------------------|
| Design of the product                       | Single device round         |
| Enclosure:                                  |                             |
| Number of command points                    | 1                           |
| Actuator:                                   |                             |
| Design of the operating mechanism           | selector switch             |
| Manner of function of the actuating element | Latching                    |
| Product extension optional Light source     | No                          |
| Color                                       |                             |
| • of the actuating element                  | Green                       |
| Material of the actuating element           | plastic                     |
| Outer diameter of the actuating element     | 28.5 mm                     |
| Type of unlocking device                    | rotate-to-unlatch mechanism |
| Number of switching positions               | 3                           |
| Actuating angle                             |                             |
| • clockwise                                 | 50°                         |
| • anticlockwise                             | 50°                         |

|                              |          |
|------------------------------|----------|
| <b>Front ring:</b>           |          |
| Product component front ring | Yes      |
| Design of the front ring     | Standard |
| Material of the front ring   | metal    |
| Color of the front ring      | silver   |

|                        |       |
|------------------------|-------|
| <b>Holder:</b>         |       |
| Material of the holder | Metal |

|                                                                     |                   |
|---------------------------------------------------------------------|-------------------|
| <b>General technical data:</b>                                      |                   |
| Product function                                                    |                   |
| • EMERGENCY OFF function                                            | No                |
| • EMERGENCY STOP function                                           | No                |
| Protection class IP                                                 | IP67              |
| Vibration resistance                                                |                   |
| • acc. to IEC 60068-2-6                                             | 20 ... 200 Hz: 5g |
| Operating frequency maximum                                         | 1 000 1/h         |
| Mechanical service life (switching cycles)                          |                   |
| • typical                                                           | 300 000           |
| Equipment marking                                                   |                   |
| • acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750 | S                 |
| • acc. to DIN EN 61346-2                                            | S                 |
| • acc. to DIN EN 81346-2                                            | S                 |

|                                                |                 |
|------------------------------------------------|-----------------|
| <b>Connections/ Terminals:</b>                 |                 |
| Tightening torque of the screws in the bracket | 1.4 ... 1.6 N·m |

|                                                           |                |
|-----------------------------------------------------------|----------------|
| <b>Ambient conditions:</b>                                |                |
| Ambient temperature                                       |                |
| • during operation                                        | -25 ... +70 °C |
| • during storage                                          | -40 ... +80 °C |
| Environmental category during operation acc. to IEC 60721 | 3K6            |

|                                            |                |
|--------------------------------------------|----------------|
| <b>Installation/ mounting/ dimensions:</b> |                |
| Mounting type                              | front mounting |
| Shape of the installation opening          | round          |
| Mounting diameter                          | 22 mm          |
| Mounting height                            | 24 mm          |
| Installation width                         | 28.5 mm        |
| Installation depth                         | 29 mm          |

|                               |  |
|-------------------------------|--|
| <b>Certificates/approvals</b> |  |
|-------------------------------|--|

| General Product Approval                                                          |                                                                                   |                                                                                   | Declaration of Conformity                                                         | Test Certificates                                                  | Shipping Approval                                                                   |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  | <a href="#">spezielle Prüfbescheinigungen</a><br><a href="#">n</a> |  |
| CSA                                                                               | UL                                                                                |                                                                                   | EG-Konf.                                                                          |                                                                    | ABS                                                                                 |

| Shipping Approval                                                                 |                                                                                   |                                                                                   |                                                                                   | other                         |                         |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------|-------------------------|
|  |  |  |  | <a href="#">Bestätigungen</a> | <a href="#">sonstig</a> |
| DNV                                                                               | LRS                                                                               | PRS                                                                               | RINA                                                                              |                               |                         |

| other                             |
|-----------------------------------|
| <a href="#">Umweltbestätigung</a> |

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB3500-2DA41-Z X90>

##### Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB3500-2DA41-Z X90>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB3500-2DA41-Z X90>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SB3500-2DA41-Z X90&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB3500-2DA41-Z X90&lang=en)



last modified:

08/18/2016