

22MM METAL ROUND ACTUATOR: SELECTOR SWITCH  
MOMENTARY CONTACT TYPE 3 SWITCH POSITIONS I-O-II NON-ILLUMINATED WITHOUT HOLDER RED, SOLVENT-RESISTANT  
NOT INSCRIBABLE WITH LASER

|                       |                     |
|-----------------------|---------------------|
| Design of the product | Single device round |
|-----------------------|---------------------|

### Enclosure:

|                          |   |
|--------------------------|---|
| Number of command points | 1 |
|--------------------------|---|

### Actuator:

|                                             |                        |
|---------------------------------------------|------------------------|
| Design of the operating mechanism           | selector switch        |
| Manner of function of the actuating element | Momentary contact type |
| Product extension optional Light source     | No                     |
| Color                                       |                        |
| • of the actuating element                  | Red                    |
| Material of the actuating element           | plastic                |
| Outer diameter of the actuating element     | 28.5 mm                |
| Type of unlocking device                    | without                |
| Number of switching positions               | 3                      |
| Actuating angle                             |                        |
| • clockwise                                 | 50°                    |
| • anticlockwise                             | 50°                    |

### Front ring:

|                              |          |
|------------------------------|----------|
| Product component front ring | Yes      |
| Design of the front ring     | Standard |
| Material of the front ring   | metal    |
| Color of the front ring      | silver   |

### General technical data:

|                                            |                   |
|--------------------------------------------|-------------------|
| Product function                           |                   |
| • EMERGENCY OFF function                   | No                |
| • EMERGENCY STOP function                  | No                |
| Protection class IP                        | IP67              |
| Vibration resistance                       |                   |
| • acc. to IEC 60068-2-6                    | 20 ... 200 Hz: 5g |
| Operating frequency maximum                | 1 000 1/h         |
| Mechanical service life (switching cycles) |                   |
| • typical                                  | 300 000           |
| Equipment marking                          |                   |

- acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750
- acc. to DIN EN 61346-2
- acc. to DIN EN 81346-2

S  
S  
S

#### Ambient conditions:

##### Ambient temperature

- during operation -25 ... +70 °C
- during storage -40 ... +80 °C

Environmental category during operation acc. to IEC 60721

3K6

#### Installation/ mounting/ dimensions:

|                                   |                |
|-----------------------------------|----------------|
| Mounting type                     | front mounting |
| Shape of the installation opening | round          |
| Mounting diameter                 | 22 mm          |
| Mounting height                   | 24 mm          |
| Installation width                | 28.5 mm        |
| Installation depth                | 29 mm          |

#### Certificates/approvals

##### General Product Approval

##### Declaration of Conformity

##### Shipping Approval



##### Shipping Approval

##### other



[Bestätigungen](#)

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB3500-2EA21-0PA0-Z B01>

##### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB3500-2EA21-0PA0-Z B01>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB3500-2EA21-0PA0-Z B01>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SB3500-2EA21-0PA0-Z B01&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB3500-2EA21-0PA0-Z B01&lang=en)

last modified:

08/18/2016