

22MM METAL ROUND ACTUATOR: SELECTOR SWITCH  
MOMENTARY CONTACT TYPE 2 SWITCH POSITIONS O-I NON-  
ILLUMINATED WITHOUT HOLDER GREEN, SOLVENT-  
RESISTANT NOT INSCRIBABLE WITH LASER

|                       |                     |
|-----------------------|---------------------|
| Design of the product | Single device round |
|-----------------------|---------------------|

### Enclosure:

|                          |   |
|--------------------------|---|
| Number of command points | 1 |
|--------------------------|---|

### Actuator:

|                                             |                        |
|---------------------------------------------|------------------------|
| Design of the operating mechanism           | selector switch        |
| Manner of function of the actuating element | Momentary contact type |
| Product extension optional Light source     | No                     |
| Color                                       |                        |
| • of the actuating element                  | Green                  |
| Material of the actuating element           | plastic                |
| Outer diameter of the actuating element     | 28.5 mm                |
| Type of unlocking device                    | without                |
| Number of switching positions               | 2                      |
| Actuating angle                             |                        |
| • clockwise                                 | 50°                    |

### Front ring:

|                              |          |
|------------------------------|----------|
| Product component front ring | Yes      |
| Design of the front ring     | Standard |
| Material of the front ring   | metal    |
| Color of the front ring      | silver   |

### General technical data:

|                                                                     |                   |
|---------------------------------------------------------------------|-------------------|
| Product function                                                    |                   |
| • EMERGENCY OFF function                                            | No                |
| • EMERGENCY STOP function                                           | No                |
| Protection class IP                                                 | IP67              |
| Vibration resistance                                                |                   |
| • acc. to IEC 60068-2-6                                             | 20 ... 200 Hz: 5g |
| Operating frequency maximum                                         | 1 000 1/h         |
| Mechanical service life (switching cycles)                          |                   |
| • typical                                                           | 300 000           |
| Equipment marking                                                   |                   |
| • acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750 | S                 |

- acc. to DIN EN 61346-2
- acc. to DIN EN 81346-2

S  
S

#### Ambient conditions:

|                                                                  |                |
|------------------------------------------------------------------|----------------|
| <b>Ambient temperature</b>                                       |                |
| • during operation                                               | -25 ... +70 °C |
| • during storage                                                 | -40 ... +80 °C |
| <b>Environmental category during operation acc. to IEC 60721</b> | 3K6            |

#### Installation/ mounting/ dimensions:

|                                          |                |
|------------------------------------------|----------------|
| <b>Mounting type</b>                     | front mounting |
| <b>Shape of the installation opening</b> | round          |
| <b>Mounting diameter</b>                 | 22 mm          |
| <b>Mounting height</b>                   | 24 mm          |
| <b>Installation width</b>                | 28.5 mm        |
| <b>Installation depth</b>                | 29 mm          |

#### Certificates/approvals

| General Product Approval                                                                  | Declaration of Conformity                                                                      | Shipping Approval                                                                           |
|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| <br>CSA | <br>UL       | <br>EAC   |
|                                                                                           | <br>EG-Konf. | <br>ABS |
|                                                                                           |                                                                                                | <br>DNV |

| Shipping Approval                                                                           | other                         |
|---------------------------------------------------------------------------------------------|-------------------------------|
| <br>LRS  | <a href="#">Bestätigungen</a> |
| <br>PRS  |                               |
| <br>RINA |                               |

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB3500-2LA41-0PA0-Z B01>

##### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB3500-2LA41-0PA0-Z B01>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB3500-2LA41-0PA0-Z B01>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SB3500-2LA41-0PA0-Z B01&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB3500-2LA41-0PA0-Z B01&lang=en)

last modified:

08/18/2016