


22MM METAL ROUND ACTUATOR: OMR KEY-
OPER.SWITCH W. 2 KEYS LATCHING 2 SWITCH
POSITIONS O-I LOCK NO 73038,
REMOVAL POS. I WITH HOLDER LIGHT BLUE



Actuator:		
Design of the product		Single device round
Design of the operating mechanism		Key-operated switch
External diameter / of the activation element	mm	28.5
Functionality / of the actuator		Latching
Type of unlocking device		key unlatching
Color / of the activation element		Light blue
Material / of the activation element		plastic
Make of the lock		O.M.R.
Number of switching positions		2
Switch position for key distraction		I
Actuating angle		
• clockwise	°	50
Product component / front ring		Yes
Material / of the front ring		metal
Color / of the front ring		silver
Design of the front ring		Standard
Product function / EMERGENCY STOP function		No

Holder:

Material / of the holder		Metal
General technical data:		
Resistance against shock for devices without incandescent lamp / according to IEC 60068-2-27		<= 50g
Resistance against vibration / according to IEC 60068-2-6		20 ... 200 Hz: 5g
Operating cycles / maximum	1/h	1,000
Mechanical operating cycles as operating time / typical		300,000
Product extension / optional / fluorescent materials		No
Reference code - according to DIN EN 61346-2 - according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		S S
Tightening torque / of the screws in the bracket / maximum	N·m	1
Ambient temperature - during operating - during storage	°C °C	-25 ... +70 -40 ... +80
Protection class IP		IP67
climatic class / during the operating phase / according to EN 60721		3K6
Mounting type		front mounting
Shape / of the installation hole		round
Installation width	mm	28.5
Mounting diameter	mm	22
Mounting height	mm	64
Mounting depth	mm	29
Certificates/ approvals:		
General Product Approval	Declaration of Conformity	Test Certificates
 CSA  EAC  UL  EG-Konf. Special Test Certificate		
Shipping Approval		
 ABS  DNV  LRS  PRS  RINA		
other		
Confirmation	other	Environmental Confirmations
Further information:		



last change:

Jul 7, 2014