




22MM METAL ROUND ACTUATOR: SELECTOR SWITCH
LONG HANDLE MOMENTARY CONTACT TYPE 3 SWITCH
POSITIONS I-O-II NON-ILLUMINATED WITH HOLDER
WHITE

Actuator:		
Design of the product		Single device round
Design of the operating mechanism		selector switch
External diameter / of the activation element	mm	28.5
Functionality / of the actuator		Momentary contact type
Type of unlocking device		without
Color / of the activation element		White
Material / of the activation element		plastic
Shape / of the activation element		Extended handle
Number of switching positions		3
Actuating angle		
• clockwise	°	50
• anticlockwise	°	50
Product component / front ring		Yes
Material / of the front ring		metal
Color / of the front ring		silver
Design of the front ring		Standard
Product function / EMERGENCY STOP function		No

Holder:

Material / of the holder		Metal
General technical data:		
Resistance against shock		<= 50g
for devices without incandescent lamp / according to IEC 60068-2-27		
Resistance against vibration / according to IEC 60068-2-6		20 ... 200 Hz: 5g
Operating cycles / maximum	1/h	1,000
Mechanical operating cycles as operating time / typical		300,000
Product extension / optional / fluorescent materials		No
Reference code		S
- according to DIN EN 61346-2 - according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		S
Tightening torque / of the screws in the bracket / maximum	N·m	1
Ambient temperature		
during operating	°C	-25 ... +70
during storage	°C	-40 ... +80
Protection class IP		IP67
climatic class / during the operating phase / according to EN 60721		3K6
Mounting type		front mounting
Shape / of the installation hole		round
Installation width	mm	37
Mounting diameter	mm	22
Mounting height	mm	28
Mounting depth	mm	29
Certificates/ approvals:		
General Product Approval	Declaration of Conformity	Test Certificates
 CSA  EAC  UL  CE EG-Konf. Special Test Certificate		
Shipping Approval		
 ABS  DNV  LRS  PRS  RINA		
other		
Confirmation	other	Environmental Confirmations
Further information:		



last change:

Jul 7, 2014