

LOCK, 2 POSITIONS, MOMENT.- CONTACT TYPE ON THE LEFT, W/HOLDER, PACKED, METAL, Z= HOLDER

Design of the product	Single device round
-----------------------	---------------------

### Enclosure:

Number of command points	1
--------------------------	---

### Actuator:

Design of the operating mechanism	Key-operated switch
Manner of function of the actuating element	Momentary contact type
Product extension optional Light source	No
Color	
• of the actuating element	Silver
Material of the actuating element	metal
Outer diameter of the actuating element	28.5 mm
Type of unlocking device	without
Number of switching positions	2
Switch position for key distraction	O
Actuating angle	
• clockwise	50°
Lock make	RONIS

### Front ring:

Product component front ring	Yes
Design of the front ring	Standard
Material of the front ring	metal
Color of the front ring	silver

### General technical data:

Product function	
• EMERGENCY OFF function	No
• EMERGENCY STOP function	No
Protection class IP	IP67
Vibration resistance	
• acc. to IEC 60068-2-6	20 ... 200 Hz: 5g
Operating frequency maximum	1 000 1/h
Mechanical service life (switching cycles)	
• typical	300 000
Equipment marking	
• acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	S

- acc. to DIN EN 61346-2
- acc. to DIN EN 81346-2

S  
S

#### Ambient conditions:


<b>Ambient temperature</b>	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
<b>Environmental category during operation acc. to IEC 60721</b>	3K6

#### Installation/ mounting/ dimensions:

<b>Mounting type</b>	front mounting
<b>Shape of the installation opening</b>	round
<b>Mounting diameter</b>	22 mm
<b>Mounting height</b>	44 mm
<b>Installation width</b>	28.5 mm
<b>Installation depth</b>	29 mm

#### Certificates/approvals

General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval
 CSA  UL  EAC  CE EG-Konf.	<a href="#">spezielle Prüfbescheinigung</a> n	 ABS	

Shipping Approval	other
 DNV  LRS  PRS  RINA	<a href="#">Umweltbestätigung</a> <a href="#">Bestätigungen</a>

other
<a href="#">sonstig</a>

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3SB3500-4CD01-Z B01>

##### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3SB3500-4CD01-Z B01>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3SB3500-4CD01-Z B01>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SB3500-4CD01-Z B01&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB3500-4CD01-Z B01&lang=en)

**last modified:**

08/18/2016