

ENCLOSURE FOR COMMAND DEVICES, 22MM,
ROUND, ENCLOSURE MATERIAL PLASTIC,
ENCLOSURE TOP PART YELLOW,
1 COMMAND POSITION,
A=EMERGEN.-STOP MUSHROOM PUSHBUTTON RED,
40MM, ROTATE-TO-UNLATCH,
SAFETY LOCK RONIS SB30, 1NC, 1NC,
SCREW CONNECTION, FLOOR MOUNTING,
1 X M20 EACH AT TOP AND BOTTOM

Enclosure:

Design of the enclosure		Enclosure for command and signaling devices with standard equipment
Material / of the enclosure		plastic
Color / of top part of the enclosure		yellow
Number of Command Points		1
Product component / protective collar		No
Form / of the enclosure front		Square
Design of electrical connection / on enclosure		Cable routing above and below, both 1 x M20
Mounting type / of enclosure		Vertical
Product function / EMERGENCY STOP function		Yes

Actuato/ signaling device:

Design of the operating mechanism		EMERGENCY STOP mushroom pushbutton with lock
Assembling of the commanding and signaling device		A = Emergency stop mushroom pushbutton with lock
Number of mushroom pushbuttons		1
Number of indicator lights		0
Number of pushbuttons		0
Number of key-operated switches		0
Color / of the activation element		Red
Material / of the activation element		plastic
Product component / front ring		No
Type of unlocking device		rotate-to-unlatch mechanism

Holder:

Material / of the holder		Plastic
--------------------------	--	---------

Contact block/ lampholder:

Number of switching elements		2
------------------------------	--	---

Number of NC contacts / for auxiliary contacts		2
Number of NO contacts / for auxiliary contacts		0
Number of changeover contacts / for auxiliary contacts		0
Product function / positive opening		Yes
Number of lampholders		0
Mounting type / of contact blocks, socket, and accessories		Floor mounting
Design of electrical connection / of contact blocks, socket, and accessories		Screw-type terminal
Product component / fluorescent materials		No
Product extension / optional / fluorescent materials		No

Accessories:

Number of backing plates		0
Number of labeling plates		0
Product component / holder for 3 switching elements		No

General technical details:

Voltage type / of operating voltage		AC/DC
Operating voltage • for DC • rated value • 1 / for DC / rated value • at 50 Hz / at AC • rated value • 1 / at 50 Hz / for AC / rated value • at 60 Hz / at AC • rated value • 1 / at 60 Hz / for AC / rated value	V V V V V V	5 ... 230 230 5 ... 400 400 5 ... 300 300
Operating current • at AC-12 • at 24 V / rated value • at 48 V / rated value • at 110 V / rated value • at 230 V / rated value • at 400 V / rated value • at AC-15 • at 24 V / rated value • at 48 V / rated value • at 110 V / rated value • at 230 V / rated value • at 400 V / rated value	A A A A A A A A A A	10 10 10 10 10 6 6 6 6 3

• at DC-12 • at 24 V / rated value • at 48 V / rated value • at 110 V / rated value • at 230 V / rated value • at DC-13 • at 24 V / rated value • at 48 V / rated value • at 110 V / rated value • at 230 V / rated value	A	10
	A	5
	A	2.5
	A	1
	A	3
	A	1.5
	A	0.7
	A	0.3
Delivery state / pre-wired on strip terminal		No
Product component / stand/pedestal		No
Resistance against shock • for devices without incandescent lamp / according to IEC 60068-2-27		<= 50g
Resistance against vibration / according to IEC 60068-2-6		20 ... 200 Hz: 5g
Reference code • according to DIN EN 61346-2 • according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		S S
Tightening torque / of the screws in the bracket / maximum	N·m	1
Ambient temperature • during operating • during storage	°C °C	-25 ... +70 -40 ... +80
Protection class IP		IP65
B10 value / with high demand rate / according to SN 31920		100,000
Proportion of dangerous failures / with high demand rate / according to SN 31920	%	20
Proportion of dangerous failures / with low demand rate / according to SN 31920	%	20
Failure rate [FIT] / with low demand rate / according to SN 31920	FIT	100
T1 value / for proof test interval or service life / according to IEC 61508	a	20
climatic class / during the operating phase / according to EN 60721		3K6
Shape / of the installation hole		round
Mounting diameter	mm	22
Width	mm	85
Height	mm	85
Depth	mm	64

Certificates/ approvals:

General Product Approval	Declaration of Conformity	Test Certificates		
	 EG-Konf.	Special Test Certificate		
Shipping Approval				
 ABS	 DNV	 LRS	 PRS	 RINA
other				
Confirmation	other	Environmental Confirmations		

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)
<http://www.siemens.com/industrial-controls/mall>

Cax online generator
<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<http://support.automation.siemens.com/WW/view/en/3SB3801-0GK20-2AB0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SB3801-0GK20-2AB0

last change:

Jul 7, 2014