

ENCLOSURE FOR 22MM PROGRAM PLASTIC VERSION
 3 COMMAND POSITIONS GRAY TOP PART
 A=PUSHBUTTON RED,
 LABEL "O" 1NC B=PUSHBUTTON BLACK,LABEL"I" 1NO
 C=PUSHBUTTON BLACK 1NO,
 WITH LABEL "II"

Enclosure:

Design of the enclosure		Enclosure for command and signaling devices with standard equipment
Material / of the enclosure		plastic
Color / of top part of the enclosure		grey
Number of Command Points		3
Product component / protective collar		No
Form / of the enclosure front		rectangular
Design of electrical connection / on enclosure		Cable routing above and below, both 1 x M20
Type of mounting / of enclosure		Vertical
Product function / EMERGENCY STOP function		No

Actuator / signaling device:

Design of the operating mechanism		Pushbutton
Assembling of the commanding and signaling device		A = Pushbutton / B = Pushbutton / C = Pushbutton
Number of mushroom pushbuttons		0
Number of indicator lights		0
Number of pushbuttons		3
Number of key-operated switches		0
Material / of the activation element		plastic
Product component / front ring		Yes
Material / of the front ring		plastic
Color / of the front ring		black
Type of unlocking device		without

Holder:

Material / of the holder		Plastic
---------------------------------	--	---------

Contact block / lampholder

Number of switching elements		3
Number of NC contacts / for auxiliary contacts		1

Number of NO contacts / for auxiliary contacts	2
Number of change-over switches / for auxiliary contacts	0
Product function / positive opening	Yes
Number of lampholders	0
Type of fixing/fixation / for contact blocks	Floor mounting
Design of electrical connection / of contact blocks, socket, and accessories	Screw-type terminal
Product component / fluorescent materials	No
Product extension / optional / fluorescent materials	No

Accessories:

Number of backing plates	0
Number of labeling plates	3
Labeling / of the name plate for command devices	A = O / B = I / C = II
Color / of labeling plate	Black
Product component / holder for 3 switching elements	No

General technical details:

Type of voltage / of the operating voltage		AC/DC
Operating voltage		
• for DC		
• rated value	V	5 ... 230
• 1 / for DC / rated value	V	230
• at 50 Hz / at AC		
• rated value	V	5 ... 400
• 1 / at 50 Hz / for AC / rated value	V	400
• at 60 Hz / at AC		
• rated value	V	5 ... 300
• 1 / at 60 Hz / for AC / rated value	V	300
Operating current		
• at AC-12		
• at 24 V / rated value	A	10
• at 48 V / rated value	A	10
• at 110 V / rated value	A	10
• at 230 V / rated value	A	10
• at 400 V / rated value	A	10
• at AC-15		
• at 24 V / rated value	A	6
• at 48 V / rated value	A	6
• at 110 V / rated value	A	6
• at 230 V / rated value	A	6

<ul style="list-style-type: none"> • at 400 V / rated value 	A	3
<ul style="list-style-type: none"> • at DC-12 		
<ul style="list-style-type: none"> • at 24 V / rated value 	A	10
<ul style="list-style-type: none"> • at 48 V / rated value 	A	5
<ul style="list-style-type: none"> • at 110 V / rated value 	A	2.5
<ul style="list-style-type: none"> • at 230 V / rated value 	A	1
<ul style="list-style-type: none"> • at DC-13 		
<ul style="list-style-type: none"> • at 24 V / rated value 	A	3
<ul style="list-style-type: none"> • at 48 V / rated value 	A	1.5
<ul style="list-style-type: none"> • at 110 V / rated value 	A	0.7
<ul style="list-style-type: none"> • at 230 V / rated value 	A	0.3
Delivery state / pre-wired on strip terminal		No
Product component / stand/pedestal		No
Resistance against shock		
<ul style="list-style-type: none"> • for devices without incandescent lamp / according to IEC 60068-2-27 		<= 50g
Resistance against vibration / according to IEC 60068-2-6		20 ... 200 Hz: 5g
Item designation		
<ul style="list-style-type: none"> • according to DIN EN 61346-2 		S
<ul style="list-style-type: none"> • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 		S
Tightening torque / of the screws in the bracket / maximum	N·m	1
Ambient temperature		
<ul style="list-style-type: none"> • during operating 	°C	-25 ... +70
<ul style="list-style-type: none"> • during storage 	°C	-40 ... +80
Protection class IP		IP65
climatic class / during the operating phase / according to EN 60721		3K6
Shape / of the installation hole		round
Mounting diameter	mm	22
Width	mm	85
Height	mm	154
Depth	mm	64

Certificates/approvals:

General Product Approval				Declaration of Conformity	Test Certificates
 CSA	 GOST	 UL	 EG-Konf.	Special Test Certificate	
Shipping Approval				other	
 ABS	 DNV	 LRS	 PRS	Confirmation	Environmental Confirmations

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SB3803-0DB3/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SB3803-0DB3

last change:

Feb 8, 2013