SIEMENS

Product data sheet 3SE2257-6XX40



SAFETY POSITION SWITCH WITH SEPARATE ACTUATOR,
MOULDED-PLASTIC ENCLOSED,
SHORT ENCLOSURE,
3X(M20X1.5) OPERATION FROM THE SIDE AND AND THE FRONT 1NC,
PULLING FORCE 5N,
DELIVERED WITHOUT ACTUATOR

General technical details:			
product designation	safety position switch		
Active principle	mechanical		
Product function / status display	No		
Design of the interface / for safety-related communication	without		
Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750	S		
Item designation / according to DIN EN 61346-2	В		
item designation / according to DIN EN 61346-2	В		

Enclosure:			
Design of the housing		wide	
Design of the housing / according to standard		No	
Coating / of the enclosure		Other types	
Material / of the enclosure		glass fiber reinforced thermoplast	
Length of the sensor	mm	75	
Width of the sensor	mm	52	

Drive Head:	
Design of the operating mechanism	without

Contact:	
Design of the contact element	slow-action contacts

Number of NC contacts / for auxiliary contacts Number of NO contacts / for auxiliary contacts Number of change-over switches / for auxiliary contacts Design of the switching function Design of the electrical connection Ambient conditions: Protection class IP Certificates/approvals: Verification of suitability Acceptability for application / safety cut-out switch Explosion protection category for gas		0 1 0 positive opening screw-type terminals
Number of change-over switches / for auxiliary contacts Design of the switching function Design of the electrical connection Ambient conditions: Protection class IP Certificates/approvals: Verification of suitability Acceptability for application / safety cut-out switch Explosion protection category for gas		positive opening screw-type terminals
Design of the switching function Design of the electrical connection Ambient conditions: Protection class IP Certificates/approvals: Verification of suitability Acceptability for application / safety cut-out switch Explosion protection category for gas		positive opening screw-type terminals
Design of the electrical connection Ambient conditions: Protection class IP Certificates/approvals: Verification of suitability Acceptability for application / safety cut-out switch Explosion protection category for gas		screw-type terminals
Ambient conditions: Protection class IP Certificates/approvals: Verification of suitability Acceptability for application / safety cut-out switch Explosion protection category for gas		
Protection class IP Certificates/approvals: Verification of suitability Acceptability for application / safety cut-out switch Explosion protection category for gas		IP65
Certificates/approvals: Verification of suitability Acceptability for application / safety cut-out switch Explosion protection category for gas		IP65
Verification of suitability Acceptability for application / safety cut-out switch Explosion protection category for gas		
Acceptability for application / safety cut-out switch Explosion protection category for gas		
Explosion protection category for gas		CE / UL / CSA / CCC
		Yes
		none
Explosion protection category for dust		none
Ambient temperature		
during operating	°C	8530
General Product Approval	Declaration	n of Conformity
CSA GOST UL	EG-Konf.	
Shipping Approval		other
ABS LRS PRS	RINA	<u>Confirmation</u> <u>other</u>
Further information:		

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrial-controls/mall

CAx-Online-Generator

http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/3SE2257-6XX40/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

 $\underline{\text{http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SE2257-6XX40}$

last change: Jan 21, 2013