



SAFETY SWITCH WITH UNLOCKING BUTTON CABLE
ENTRY M20X1,5 IP65,2NO+2NC WITH CAP

General technical details:

Product designation		safety foot switch
Product equipment / interlock		Yes
Product equipment / notch		Yes
Product component / covering		Yes
Operating current / at AC-15 / at 230 V / rated value	A	6
Number of switching steps		2
Number of the activation pedals		1
Reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		S
Reference code / according to DIN EN 61346-2		S
Mounting type		screw fixing

Enclosure:

Material / of the enclosure		metal
Color / of the housing		black
Color / of top part of the enclosure		grey
Color		grey-black
Width	mm	156
Height	mm	264
Depth	mm	140

Contact:

Number of NC contacts / for auxiliary contacts		2
Number of NO contacts / for auxiliary contacts		2
Cable gland version		M20 x 1.5

Ambient conditions:

Protection class IP		IP65
Ambient temperature / during operating	°C	80
Ambient temperature / during operating	°C	-25

Certificates/approvals:

Suitability for use / safety cut-out switch		Yes
---	--	-----

General Product Approval**Declaration of Conformity**

CCC



CSA



EG-Konf.

Shipping Approval**other**

ABS



LRS



PRS



RINA

[Confirmation](#)[other](#)**Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/industrial-controls/catalogs>**Industry Mall (Online ordering system)**<http://www.siemens.com/industrial-controls/mall>**CAX-Online-Generator**<http://www.siemens.com/cax>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<http://support.automation.siemens.com/WW/view/en/3SE2924-3AA20/all>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SE2924-3AA20

last change:

Jan 21, 2013