

FOOT-OPERATED PUSHBUTTON TWO PEDALS,
CABLE ENTRY M20X1,5 WITHOUT IP65,
1NO+1NC



General technical details:

Product designation		momentary-contact foot switch
Product equipment / interlock		No
Product equipment / notch		No
Product component / covering		No
Operating current / at AC-15 / at 230 V / rated value	A	16
Number of switching steps		1
Number of the activation pedals		2
Reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		S
Reference code / according to DIN EN 61346-2		S
Mounting type		screw fixing

Enclosure:

Material / of the enclosure		metal
Color / of the housing		black
Color / of top part of the enclosure		grey
Color		grey-black
Width	mm	193
Height	mm	221
Depth	mm	63

Contact:

Number of NC contacts / for auxiliary contacts

2

Number of NO contacts / for auxiliary contacts

2

Cable gland version

M25 x 1.5

Ambient conditions:

Protection class IP

IP65

Ambient temperature / during operating

°C

80

Ambient temperature / during operating

°C

-25

Certificates/approvals:

Suitability for use / safety cut-out switch

No

General Product Approval

Declaration of Conformity



CCC



CSA



EG-Konf.

Shipping Approval

other



ABS



LRS



PRS



RINA

[Confirmation](#)[other](#)**Further information:**

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAx-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SE2932-0AB20/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SE2932-0AB20

last change:

Jan 21, 2013