



ADJUSTABLE LENGTH TWIST LEVER FOR POSITION SWITCH 3SE51/52 STAINL. STEEL LEVER 100MM LONG, POSITIVE FIT (GRID HOLE) PLASTIC ROLLER 19MM, FUNCTIONAL AT -40 DEGREES

General technical data:

Product designation		actuator for part-turn actuator
Product feature		expanded temperature range, e.g. railway application
Explosion protection category for dust		none
Mechanical operating cycles as operating time • typical		15,000,000
Resistance against vibration		0.35 mm / 5g
Resistance against vibration / for railway applications / according to DIN EN 61373		Category 1, Class B
Resistance against shock		30g / 11 ms
Resistance against shock / for railway applications / according to DIN EN 61373		Category 1, Class B
Ambient temperature • during operating • during storage	°C	-40 ... +85 -40 ... +90
Design of the operating mechanism		stainless steel lever, adjustable length with closing shape, plastic roller 19 mm
mounting position		any
Fire load	kJ	64
Reference code		

- according to DIN 40719 extended according to IEC 204-2 / according to IEC 750
- according to DIN EN 61346-2

	E
	T

Certificates/ approvals:

General Product Approval		Declaration of Conformity	Test Certificates
 CSA		 UL	 EG-Konf.
other			Special Test Certificate
Confirmation	Vibration Test Certificates		

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator




<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SE5000-0AA62-1AJ0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SE5000-0AA62-1AJ0



last change:

Jun 16, 2014