



DRIVE TWIST LEVER METAL FOR POSITION SWITCH
3SE51 LE /RIGHT ADJUSTABLE,
W/O LEVER FUNCTIONAL AT -40 DEGREES

General technical details:

product designation		Semi-rotary actuator for position switch
Product feature		expanded temperature range, e.g. railway application
Explosion protection category for dust		none
Resistance against vibration		0.35 mm / 5g
Resistance against vibration / for railway applications / according to DIN EN 61373		Category 1, Class B
Resistance against shock		30g / 11 ms
Resistance against shock / for railway applications / according to DIN EN 61373		Category 1, Class B
Ambient temperature		
• during operating	°C	-40 ... +85
• during storage	°C	-40 ... +90
Material / of the enclosure		
• of the switch head		metal
Design of the operating mechanism		without
mounting position		any
Fire load	kJ	64
Item designation		
• according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		E

Certificates/approvals:

General Product Approval

Functional Safety / Safety of Machinery



Declaration of Conformity

Test Certificates

other



[Special Test
Certificate](#)

[Confirmation](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator


<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SE5000-0AH00-1AJ0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SE5000-0AH00-1AJ0



last change:

Jan 23, 2013