



TWIST LEVER ACTUATOR PLASTIC FOR POSITION SWITCH 3SE5132 ADJUSTABLE,
W/O LEVER FUNCTIONAL AT -40 DEGREES
FUNCTIONAL AT -40 DEGREES

General technical data:

Product designation		Semi-rotary actuator for position switch
Product feature		expanded temperature range, e.g. railway application
Explosion protection category for dust		none
Resistance against vibration		0.35 mm / 5g
Resistance against vibration / for railway applications / according to DIN EN 61373		Category 1, Class B
Resistance against shock		30g / 11 ms
Resistance against shock / for railway applications / according to DIN EN 61373		Category 1, Class B
Ambient temperature		
• during operating	°C	-40 ... +85
• during storage	°C	-40 ... +90
Material / of the enclosure		
• of the switch head		plastic
Design of the operating mechanism		without
mounting position		any
Fire load	kJ	358
Reference code		
• according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		E

Certificates/ approvals:

General Product Approval

Declaration of
Conformity

other



[Confirmation](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator


<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SE5000-0AJ00-1AJ0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SE5000-0AJ00-1AJ0



last change:

Jun 16, 2014