



SEPARATE STANDARD ACTUATOR FOR POS. W.
TUMBLER 3SE5312../3SE5322.. AND ASI 3SF13... AND
POS. WITH SEPARATE ACTUATOR 3SE51../3SE52.. AND
ASI 3SF11../3SF21..

General technical details:

product designation		actuator
Explosion protection category for dust		none
Mechanical operating cycles as operating time • typical		1,000,000
Resistance against vibration		0.35 mm / 5g
Resistance against shock		30g / 11 ms
Ambient temperature • during operating • during storage	°C °C	-25 ... +85 -40 ... +90
Design of the operating mechanism		Standard actuator, die cast zinc
mounting position		any
Item designation • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 • according to DIN EN 61346-2		E T

Certificates/approvals:

General Product Approval					Functional Safety / Safety of Machinery
 CCC	 CSA	 GOST	 UL	 VDE	 VDE
Declaration of Conformity	Test Certificates	other			
 EG-Konf.	Special Test Certificate	Confirmation			

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator



<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SE5000-0AV01/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SE5000-0AV01



last change:

Jan 23, 2013