



CABLE-OPERATED SWITCH METAL ENCLOSURE,
2X M20X1.5 1NO+2NC,
LATCHES ACC. TO EN ISO 13850 BUTTON RESET WITH
YELLOW COVER

General technical details:

product designation		cable-operated switch
Supply voltage / for DC / rated value		
• rated value	/ V	250
Number of indicator lights		1
Type of unlocking device		push-to-unlatch mechanism
Rope length / maximum	m	25
Product component / EMERGENCY STOP device		No
Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		S
Item designation / according to DIN EN 61346-2		S
Width	mm	52
Height	mm	171
Depth	mm	53.5

Enclosure:

Type of mounting		screw fixing
Material / of the enclosure		metal
Color / of top part of the enclosure		grey

Contact:

Number of NC contacts / for auxiliary contacts		2
Number of NO contacts / for auxiliary contacts		1
Switching function / arresting lock		Yes

Certificates/approvals:

General Product Approval	Declaration of Conformity	Shipping Approval
 CSA	 EG-Konf.	 ABS
 GOST		 PRS

Ambient conditions:

Protection class IP		IP65
Ambient temperature		
• during operating	°C	-25 ... +70

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SE7150-1BH00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SE7150-1BH00

last change:

Jan 21, 2013