

SIGUARD CABLE-OPER. SWITCH METAL HOUSING,2X
M20X1.5 1NO+1NC,
LATCHES AC.EN ISO13850 KEY UNLATCHING FOR
CABLES UP TO TO 25M

General technical details:

product designation		cable-operated switch
Number of indicator lights		0
Type of unlocking device		key unlatching
Rope length / maximum	m	25
Product component / EMERGENCY STOP device		Yes
Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		S
Item designation / according to DIN EN 61346-2		S
Width	mm	52
Height	mm	164.5
Depth	mm	57.5

Enclosure:

Type of mounting		screw fixing
Material / of the enclosure		metal
Color / of top part of the enclosure		grey

Contact:

Number of NC contacts / for auxiliary contacts		1
Number of NO contacts / for auxiliary contacts		1
Switching function / arresting lock		Yes

Certificates/approvals:

General Product Approval

Declaration of Conformity



Shipping Approval



Ambient conditions:

Protection class IP

IP65

Ambient temperature

- during operating

°C

-25 ... +70

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/industrial-controls/catalogs>**Industry Mall (Online ordering system)**<http://www.siemens.com/industrial-controls/mall>**CAX-Online-Generator**<http://www.siemens.com/cax>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<http://support.automation.siemens.com/WW/view/en/3SE7150-1CD00/all>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SE7150-1CD00**last change:**

Jan 21, 2013